



The purpose of this survey is to set the 4 corners of a 50' x 100' lot the point of beginning of which is described as being 550' North & 315' East of the SW cor of the NW 1/4 of the NW 1/4 of sec. 11, T4N, R2BE, W1M., so a house can be moved onto it.

The point of beginning that I set is 545.73' North & 316.00' East of the computed location of said SW corner. The North distance, 545.73', was used because it fits the split of curbed streets and old fence lines. The east distance, 316.00', was used because it fits fence lines & matches a survey by Fraley on BEEBE AVE. (see note).

LEGEND:

- Monuments Found
- (000) of Record.
- 1/2" x 24" I. Rods set with metal tag # 951
- x-x- fence line

REGISTERED PROFESSIONAL LAND SURVEYOR

G. Dennis Edwards

OREGON JULY 18, 1971 G. DENNIS EDWARDS 951

85-162-A

RECEIVED BY  
 Umatilla County Surveyor  
 Date 10-28-85  
 Rec'd By KA  
 No. 85-162-A

SURVEY FOR MIKE YUNKER  
 IN NW 1/4 NW 1/4 Sec 11, T4N, R2BE, W1M.  
 UMATILLA COUNTY, OREGON.  
 9/16/85 JOB # 58509053.  
 EDWARDS SURVEYING P.O. Box 763  
 567-3336 HERMISTON, OR.