chmn. and A.E. Rest. marker, and qualify each according to law. I set initial post 26 North and 30 West of S.E. Cor of Sec 16 T 4 N R 33 E. against fence on N side of road in lane E & W. I run thence on a true line bet. Secs. 15 & 16. - Var 21° E

North Ascend gently
700 ft Summit. descend gently
1120 " Draw. NE Ascend
1550 " Summit
1600 " Descend gently
1870 " Ascend from Drab. Course S.E.
2200 " Summit. Descend gently
2680 " Foot of descent; Ascend gently
2888 " ¼ Sec Cor stone bet. Secs, 15 & 16
3310 " Summit. and sharp descent
3390 " Ravine SE. Ascend mildly
4350 " Summit.
5280 " Set 1. M.S. in set 15. East of line 20 feet. Continue on line bet. Secs, 15 & 16 N.
320 " Stone cor for Secs, 9. 10. 15 & 16. Set angle post at stone cor and turn on line bet. Secs. 10 & 15
3043 " ¼ Sec Cor bet. Secs. 10 & 15 at Wm Reeder. fence N.S. E & W
4000 " Descend
5350 " Foot of Descent.
4960 " Ascent gently
5360 " Fence of W side of Road in lane N & S.
5675 " " " E " " " " " "

I cut R, on West side of post in fence. at point, and raise earth mound 4 x 4 x ½ feet around same. All the posts used were of the dimensions, and were marked and set in mounds as required by law for the same. I hereby certify that the foregoing notes of road survey No 335 for Umatilla. Co. Oregon, are correct.

Jno. C. Arnold. Surveyor.

Filed May 7th 1890
G.A. Hartman. Clerk