

Thence N 65° W	386	1064	A 14
" N 44° 30' E	310	1374	15
" North	3722	5096	16
" East	2904	8000	Set post 4 inches square and 4 feet long 30 feet North of point marked "B.M.", Built mound 4 feet wide at base and 18 inches high; dug pits East and West from post.
Thence East	950		17
" N 41° 30' E	225	1175	18
" North	2992	4167	19
" N 56° W	235	4402	20
" N 26° W	390	4792	21
" N 45° E	390	5182	22
" North	2730	7912	23
" N 16° E	.88	80.00	Set post 4 inches square and 4 feet long 30 feet West of point, Marked "M"; Built mound 4 feet wide at base and 18 inches high; dug pits N and S from post.
Thence N 16° E	2312		24
" N 1° 10' W	300	2612	25
" N 20° 15' W	152	2764	26
" N 36° 15' W	471	3235	27
" N 9° 45' W	1392	4627	28
" N 32° 45' E	212	4839	29
" N 31° W	502	5341	30
" N 1° E	230	5571	31
" N 48° W	790	6361	
" N 15° 30' W	280	6641	
" N 41° 30' W	1367	8008	Set post 4 inches square and 4 feet long marked "P.T. 487", Near NW corner of Cannon Station warehouse, Built mound 4 feet wide at base and 18 inches high around post

I hereby certify that the above is a true transcript of field notes of Road No. 487, as surveyed by me on the 25th day of June 1897

John W. Kumbrell

Surveyor for Umatilla County, Oregon

Filed June 28th 1897

B. B. Burroughs, Clerk