

and impartially discharge the duties of our appointments,

We called to our aid R Dick }
6 Davis } Chainmen

G W Kimbrell, Marker

Who were by the Surveyor, each, duly sworn. We viewed, surveyed and located said Road N^o 500, as specified in our order, and find the route practicable and would most respectfully recommend the same be established a public highway of Unadilla County, Oregon

Lewis J. Gault }
Herbert Boylen } Viewers Road Survey N^o 500
J D Naugh }

Field Notes of Road N^o 500

I commenced at a point on Range line between Ranges 32 and 33 East, Twp N^o 2 South, Set Stone 24 x 9 x 8 inches 30' South of initial point marked R 500, built Stone mound around stone.

Angle	Chains	Distance		F.T.
Thence S 59° E	674		L R	1
• N 89° E	627	1301	32°	2
• S 71° E	1607	2908	20°	3
• S 81° E	485	3393	10°	4
• N 79° E	285	3678	20°	5
• S 74° E	607	4285	27°	6
• S 47° E	692	4977	27°	7
• S 68° 30' E	263	5240	21° 30'	8
• S 55° E	410	5650	13° 30'	9
• S 72° E	675	6325	17°	10
• S 56° E	350	6675	14°	11
• N 81° E	370	7045	13°	12
• S 76° E	185	7230	23°	13
• S 87° E	323	7553	11°	14
• S 67° E	447	8000	20°	15
Thence S 40° E	215		27°	16
• S 86° E	317	532	28°	17
• S 81° E	312	844	13°	18
• N 45° E	388	1732	56°	19
• S 80° E	495	1727	55°	20
• S 89° E	482	2209	9°	21
• S 75° E	795	3004	14°	22
• S 53° E	710	3714	22°	23
• S 86° 30' E	520	4234	33° 30'	24
• S 58° E	432	4666	28° 30'	25
• S 89° E	667	5333	31°	26

1 Mile. Marked a Cottonwood 18 inches 20' left Marked 1 M

rd. surveyed
would most
the road be
terminus of
ins includes
nder any cir-
Survey N^o 370
township N^o 1
g, Marked R
around post.
ked 1 M, dug
It marked
the N^o 1/4 Sec
raph pole mark
round around it,
the Field Notes
October 1898,
Oregon
ook N^o 1)
N^o 500
County:
nd locate Road
of the Honor-
at Plat Rock
m do faithfully