

2 N, R 32, Sec. 10

Sw^B NW¹⁰

Field Notes

Survey for Anthony
Cavanagh

Land located in NW $\frac{1}{4}$
of Sec 10 Twn 2 N R 32 E
W.M. Umatilla County,
Pendleton, Ore.

Date: Jan 3, 1955

Weather: Clear, Temp 30° F

Wallace: Chief of Party

Snyder: Head Chainman

Painter: Rear Chainman

I located the center
Twn 2 N; R 32 E of W.M.
by an Iron pipe. This
and also the NE Corner
tract of land. Thence I
and found another Iron
corner of a tract of
Cavanagh. Thence I turned
 $90^{\circ}14'$ to the left and
99.8 feet and found
all of these pipes in
other monuments in conflict,
for control. The city
monuments and accepted
location. I then proceeded
distance of 46.2 feet
I then occupied this
easterly a distance of
of sight which was set
center of NW $\frac{1}{4}$ of sec. 10
set another Iron pipe.
 $89^{\circ}46'$ to the left. Then
of 146° to the center
10, Twn 2 N; R 32 E W.M.

of the N.W. $\frac{1}{4}$ of Sec 10,
This point was identified
was the point of beginning
of Anthony Cavanagh's
went West 373° feet
pipe, this being the N.W.
Land owned by Anthony
a deflection angle of
chained a distance of
another Iron pipe. Finding
good condition and no
I used these monuments
Engineer looked over these
them for property line
by extending line a
and set a iron pipe.
point and chained
 373° feet on a line
 146° feet South of the
Twn 2 N; R 32 E W.M. and
The deflection angle was
I chained a distance
of the NW $\frac{1}{4}$ of Sec
closing the survey.

Stanley J. Hall