



NOTES:

1. Bearings are based on a bearing of $N89^{\circ}20'00''W$ for the Southerly line of Section 24.
2. Searched for stone found by C.W. Cole, June 15, 1940 at $23^{\circ}24'$. Stone not found. GLO notes do not mention a stone w/"x" at this corner.
3. The $S\frac{1}{2}$ $23^{\circ}24'$ as set by Murns was found, but not checked.

LEGEND:

- denotes monuments found as noted
- denotes set $\frac{5}{8}$ in. x 30 in. iron pin
- () denotes Murns distance or bearing from a Survey for Joe Webster dated March 7, 1919.

RECEIVED BY
 Umatilla County Surveyor
 Date 11-7-79
 Rec'd By mjj
 No. 2-1203-B

REGISTERED PROFESSIONAL LAND SURVEYOR
 David H. Krumben
 OREGON
 JULY 17, 1979
 DAVID H. KRUMBEIN
 933

KRUMBEIN ENGINEERING CO. ENGINEERS - SURVEYORS - PLANNERS 221 S. Main, Pendleton, Oregon	SCALE 1" = 400'
	DATE Oct. 12, 1979
Survey for HOSKINS Section 24, T6N, R34E, W.M.	
DRN BY T.A.G.	CHKD BY J.H.B.
DRNG NO. 79-66C	