

## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

Corner established in 1882 by Herman D. Gradon, US Deputy Surveyor, under Contract Number 452. The Surveyor General's records state:

Set a basalt stone 14x7x6 ins 9 ins in the ground for 1/4 sec. cor. marked 1/4 on N-face from which

A pine 22 ins. diam., bears N.43°W., 53 lks. dist., mkd 1/4 S BT.  
 A pine 22 ins. diam., bears S.73°W., 58 lks. dist., mkd 1/4 S BT.

The 1/4 section was monumented in 1998, by Kaiser/Griffin/ Seibold, Cadastral Surveyors under Bureau of Land Management Group No. 1844. The field notes state.

The 1/4 sec. cor. of secs. 32 and 5, determined at record distance from the remains of the original bearing trees:  
 A ponderosa pine, 28 ins. diam., bears S.76-3/4°W., 58 lks. dist., with curved scribe mark visible on partially opened blaze.  
 A sawed pine stump, 22 ins. diam., bears N.42°W., 53 lks. dist., no marks.

At the corner point, set a stainless steel post, 28 ins. long, 2-1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap. From which a new bearing tree  
 A ponderosa pine, 10 ins. diam., bears N.16-1/2°E., 184 lks. dist., mkd. 1/4S32BT

Deposited a magnet in a white plastic case at the base of the stainless steel post.

**Description of corner evidence found:**


Found 3-1/4" BLM brass cap marked per the diagram, 0.3 inch above the ground, in a cow trail.

28" Ponderosa pine S.77°W., 38.3 feet (1882 Bearing Tree).  
 9" Ponderosa pine N.16°30'E., 121.4 feet (BLM Bearing Tree).  
 The BLM record, sawed pine stump, 22 ins. diam., bears N.42°W., 53 lks. dist., no marks." was not noted in the fieldnotes

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set 5/8 x 24 inch rebar with 1-1/2 inch aluminum cap, bears N.43°E., 28.3 feet, stamped WSI/RM 28.3, 2535.  
 Set 5/8x 24 inch rebar with 1-1/2 inch aluminum cap, bears S.24°W., 25.4 feet, stamped WSI/RM 25.4, 2535.

Reference monuments have an arrow pointing towards the corner. Appropriate signs have been attached to all bearing trees as required by this US Forest Service contract. 20° declination was used. Fieldwork was performed in July and August 2002.



Prepared by: White Shield, Inc.  
 2515 W. Falls Ave.  
 Kennewick, WA 99336

Michael P. LeJeune,  
 Oregon PLS. 2535

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Michael P. LeJeune*

OREGON 11/06/02  
 JAN. 21, 1992  
 MICHAEL P. LE JEUNE  
 2535  
 Expires 12/31/02

Office of ....County Surveyor....., County of ....Umatilla.....,State of Oregon, I hereby certify that the within instrument) was filed in this office for record on the .....day of .....

*David H. ...*  
 (County Official)

by .....  
 (Deputy)

**RECEIVED BY**

Umatilla County Surveyor

Date 11-02

Rec'd By KK

No. 02-273-B