


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

1882, Herman D. Graddon, U.S. Deputy Surveyor, while subdividing the township under GLO Contract No. 452 established the corner as follows:
 Set a basalt stone 12 X 12 X 4 ins in the ground, for 1/4 sec cor, marked 1/4 on N. face, from which
 A fir 7 ins diam, bears N. 40° W. 21 lks dist, marked 1/4 S.B.T.
 A fir 8 ins diam, bears S. 20° W. 17 lks dist, marked 1/4 S.B.T.

N-11
 340400
 T. 1 N., R. 36 E.
 1/4 corner of sections 16 & 21



1997-99, Kaiser, Griffin and Seibold, BLM Cadastral Surveyors, reestablish the corner as follows. Point for the 1/4 sec. cor. of secs. 16 and 21, determined at deed record bearing and distance from the aforementioned fence cor. located on the westerly right-of-way of the Union Pacific Railroad. The original cor. was in existence at the time of the deed from John H. and Bridgit McLaughlin to Oregon Railroad and Navigation Co., dated July 27, 1901 (Deed book 36, page 344); the deed from M.T. and Ethel McLaughlin to Oregon Railroad and Navigation Co. dated August 29, 1923 (Deed book 121, page 609); and the deed from Martin and Tillie McLaughlin to Oregon Railroad and Navigation Co. dated October 17, 1923 (Deed book 123, page 84). The cor. is also shown on the railroad plan map that was attached to the 1901 deed. The deed distance of 996.7 ft. from the 1/4 sec. cor. 16 and 21 to the westerly right-of-way of the Union Pacific Railroad is what was held: there is no remaining evidence of the original cor. This method best replaces the 1/4 sec. cor. of secs. 16 and 21 to its original location. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap from which:
 A ponderosa pine, 18 ins. diam. bears S. 29 1/2° E., 12 lks. dist., mkd. 1/4 S21 BT.
 A ponderosa pine, 24 ins. diam. bears N. 1° W., 72 lks. dist., mkd. 1/4 S16 BT.
 Deposit a magnet in a white plastic case at the base of the stainless steel post.

N-11

2000, David L. Haddock, Registered Land Surveyor 852, while surveying in sections 21 and 22 for the Umatilla N.F., finds the original BT's for the 1/4 corner of sections 16 & 21. This makes the BLM monument an erroneously established corner.

2001, Richard S. Kaiser, BLM Cadastral Surveyor, corrects the BLM's corner as follows:

The 1/4 sec. cor. of secs. 16 and 21, determined at record distance from the remains of the original bearing trees:
 A root hole, bears S. 12° W., 11.2 ft. dist., alongside of which is lying a fir, 28 ins. diam., with illegible scribe marks visible on a partially opened blaze. (Record: S. 20° W.)
 A Douglas fir 26 ins. diam., bears N. 69 3/4° W. 13.9 ft. dist., with scribe marks 4 S visible on partially opened blaze. (Record: N. 40° W.)
 From this point, the 1/4 sec. cor. of secs. 16 and 21, erroneously established by Kaiser, Griffin, and Seibold in 1997-99, bears N. 75°05'07" W., 21.79 ft. dist.; monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. and witnessed as described in the official record. Remove the stainless steel post and magnet and at the true corner point Reset the stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap from which the bearing tree mkd. by Kaiser, Griffin, and Seibold
 A ponderosa pine, 18 ins. diam., bears N. 22 1/2° W., 57.2 ft. dist., with scribe marks 1/4 S16 BT visible on partially healed blaze.
 and a new bearing trees
 A Douglas fir, 21 ins. diam., bears S. 34 3/4° E., 39.5 ft. dist., mkd. 1/4 S21 BT.
 Deposit a magnet in a white plastic case at the base of the stainless steel post.

Description of corner evidence found:

Found a 2 1/2" diameter stainless steel pipe, with 3 1/4" diameter brass cap, projecting 2" out of the ground, marked as shown, from which:
 21" Douglas Fir bears S 35 1/4° E, 39.5 feet, with scribing visible on pitched over blaze.
 Root hole, with uprooted 28" Douglas Fir lying alongside, with scribing visible on sawn open blaze, record <S 12° W, 11.2 feet>.
 27" Douglas Fir bears N 70° W, 13.9 feet, with scribing visible on sawn open blaze.
 18" Ponderosa Pine bears N 22 1/2° W, 57.2 feet, with scribing visible on pitched over blaze facing S 5° W.

Description of monument and accessories I established to perpetuate the original location of this corner: **New Reference:**

17" Ponderosa Pine bears S 87 3/4° W, 17.8 feet, scribed "1/4 S21" "BT" on double blaze with 3/4" diameter brass washer stamped "RLS 2308" nailed to the lower blaze between the scribed "B T".

DATUM: NAD83(1991) Oregon High Accuracy Reference Network
 STATE PLANE COORDINATES: Oregon North Zone in International Feet
 No. Latitude Longitude Northing(Y) Easting(X)
 340400 45°33'30.98767" N. 118°19'05.51426" W. 697301.174' 8760871.592'
 Work Performed By: David A. Schlaich (RLS 2308)
 Witnessed By: Matthew Duffy
 Equipment: Topcon GPT-6005C Total Station
 Magnetic Declination: 17 1/2° East
 Date: July 31, 2002



**REGISTERED
 PROFESSIONAL
 LAND SURVEYOR**

David A. Schlaich

OREGON
 JULY 16, 1987
DAVID A. SCHLAICH
 2308

RENEWAL DATE: 06/30/2004

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 20.....
 by.....
 (COUNTY OFFICIAL) (DEPUTY)