


LAND CORNER RECORD

5680-2

1. T 25 R 34E No. Z 19 Cor. 14 Mer. W State 36 (Rectangular) N. F. 16 Dist. 6

2. Corner Status



7. Photo Identification

Photo No. _____

Ident. By: _____

8. Plane Coordinate Position Data

State _____ Zone _____

X _____

Y _____

Estab. By _____

Field Book No. _____

Where Filed _____

9. Evaluation

Authentic YesNeeds Verif. Monument NoRe-estab. X Survey _____

Land Status _____

3. Original Description _____ Vol. _____ Page _____ Where Recorded _____

4. Description of Corners: Set basalt stone 18 x 7 x 6 ins., 12 ins. in the ground for 1/4 sec. cor. From which.
A pine 16 ins. diam. brs. S. 53° E. 90 Lks. dist.
A pine 6 ins. diam. brs. N. 68° E. 127 Lks. dist.
Creek 10 lks wide, runs south 350 feet below 1/4 sec. cor.

5. Investigation Notes:

Found 12" x 18" stone marked 1/4 on north face.

18" Pine bears S 53° E 90 Lks marked 1/4 SBT. corner on open ridge top.

6. Signed D. Palmer Title T.S.O. Date 7-5-62

PERPETUATION RECORD

10. Monument:

11. Accessories

Field Book _____ Page _____

12. Set By _____ Title _____

License _____ Agency _____ Date _____

13. Recorded By _____ Volume _____ Page _____

(Agency)

(Date) (City) (County) (State)

14. Remarks: