


History of original corner establishment:  
None



Description of corner evidence found:  
None

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2" x 30" iron pipe with brass cap stamped as diagram 25" in ground from which:  
a 8" fir bears S 23 1/2° E 22.3 ft scribed C 1/4 S 34 BT  
a 10" spruce bears S 2 1/2° W 19.0 ft scribed C 1/4 S 34 BT

I nailed alum. tags stamped 951 to bottom blazes and painted blazes red. Painted red band around BT's and nailed USFS signs 54-3 and 54-9 to them.

Drove a steel fence post 5 ft east and attached a 54-9 sign.

Placed stone to top of brass cap.

I hereby certify the above corner location was perpetuated as herein described in July 1985.

*Jud Coppock*

Jud Coppock , Witness

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*G. Dennis Edwards*

OREGON  
JULY 16, 1971  
G. DENNIS EDWARDS  
951

Office of..... County of.....  
State of..... I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....  
..... by .....

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

RECEIVED BY

Umatilla County Surveyor

Date 8-26-85

Rec'd By KA

No. 85-110-R

95-C