


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. G-5

History of original corner establishment:

In 1872, under G.L.O. Contract No. 176, George Williams set a post from which:

- A Spruce 6" dia. bears S26°W 170 lks.
- A White Pine 10" dia. bears S20°E 228 lks.



Description of corner evidence found:

A diligent search was made and no evidence of the original post or BTs could be found.

Description of monument and accessories I established to perpetuate the original location of this corner:

At proportioned point set 1"x30" Galvanized Pipe with 3" brass cap stamped:

Set pipe 24" in ground.

From which:

A Fir 5½" dia. bears N49½°E 85.1 ft., scribed: 1/4 S8 BT.

A Lodge Pole Pine 6" dia. bears N79°W 64.0 ft., scribed: 1/4 S7 BT.

Attached 54-3 and 54-4 signs to both BTs. Attached brass washers stamped LS 1294 to foot blaze of both BTs. Painted blazes and 6" band around both BTs. red.



I hereby certify the above corner monument was reestablished as herein described on November 11, 1980.

Witnesses: R. Orton
G. Wagoner
M. Wagoner



Office of.....County Surveyor..... County of.....Umatilla.....
 Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the.....day of.....December....., 19.....
Daniel S. Swabren, by Betty Shatto.....
 (COUNTY OFFICIAL) (DEPUTY)