


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. D-17

History of original corner establishment:  
No corner was originally set.



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:


At surveyed point set 2 1/2"x30" galvanized pipe with brass cap stamped:

Set pipe 24" in ground with mound of stone to cap.

Bearing Trees:

- A Tamarack 10" dia., bears S23°E, 59.9 ft., scribed S 1/16 S2 BT.
- A Tamarack 16" dia., bears N75°W, 36.8 ft., scribed S 1/16 S3 BT.

Attached 54-3 and 54-4 signs to both BTs. Attached brass washer stamped LS 1294 to foot blaze of both BTs. Painted blazes and 6" band around both BTs Red. Attached 54-2, 54-4 and 54-9 signs to metal post 5 ft. East of corner.



I hereby certify the above corner monument was established as herein described on July 8, 1980.

Witnesses: R. Orton  
D. Allen  
L. Huntsman



Office of.....County Surveyor..... County of.....Umatilla.....  
State of.....Oregon..... I hereby certify that the within instrument was filed in this office  
for record on the.....day of.....*December*..... 19.....*80*.....  
.....*Daniel D. Huntsman*..... by.....*Betty Shatto*.....  
(COUNTY OFFICIAL) (DEPUTY)