


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:



A 19"x 12"x4" BASALT STONE

24" PINE WEST 83 LKS.

Description of corner evidence found:

28" PINE WEST 54.8' SCRIBING VISIBLE

Description of monument and accessories established to perpetuate the original location of this corner:

SET A 2"x30" IRON PIPE WITH A BRASS-CAP MARKED: T6S R30E
 $\frac{1}{4}$
 THE CORNER MONUMENT IS SET IN A MOUND OF STONES. S11 S12
 1978
 PLS 346

14" FIR S78E 16.0' MARKED: $\frac{1}{4}$ S12 BT

THE BT'S HAVE A RED PAINTED STRIPE, BEARING TREE SIGNS, AND AN ATTENTION SIGN. THE NEW BT HAS A BRASS WASHER STAMPED PLS 346 NAILED TO THE LOWER BLAZE. THERE IS A STEEL FENCE POST WITHIN 5' OF THE CORNER.



Office of.....COUNTY...SURVEYOR..... County of.....UMATILLA.....

State of.....OREGON....., I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19..... RECEIVED SEP 11 1978

Wayne O. Harris by

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

G-21

☆ GPO 799-509

S-59-m