

USDA-FOREST SERVICE

Index

File No. A19

**CORNER RECORD (SEARCH)**

(Ref. FSM 7151.4)

Tract or Survey No. \_\_\_\_\_ Cor. No. \_\_\_\_\_

T7S R.31E

R.D. N.F. John Day County Grant

Merid Willamette

N.F. Umatilla State Oregon

**CORNER DIAGRAM**

T6S R31E

S35

1/4

S2

T7S

1980

**PHOTO IDENTIFICATION DATA**

Photo No. \_\_\_\_\_

Filed At. \_\_\_\_\_

Object Ident. \_\_\_\_\_

Ident. By \_\_\_\_\_

*Signature*

**PLANE COORDINATE POSITION DATA**

State \_\_\_\_\_ Zone \_\_\_\_\_

X \_\_\_\_\_

Y \_\_\_\_\_

Estob. By \_\_\_\_\_

*Agency*

**DESCRIBE CORNER MONUMENT FOUND**

A 3 1/4" brass cap on 2 1/2" galvanized iron pipe, in mound of earth and stone, marked as shown in diagram.

**DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND**

A 7" fallen pine snag bears N65°W-33.6 feet to stump hol  
A 17" douglas fir bears N5°W-11.4 feet with healed blaze  
A 16" douglas fir bears S58 1/2°E-41.8 feet, with partial healed blaze.  
A 24 1/2" ponderosa pine snag bears S32°E-21.1 feet.

**DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER**

Corner is 800 feet North of Highway 395 at the South end of the North Fork Bridge, roughly 1/4 mile from the USFS Work Center at Dale.

Signature

*Will R. Welch*

Title

*PLS*

Division

Headquarters

*Pendleton, OR*

Date

*11/19/94*

7100-52-(3/68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT  
Attached 54-9 sign to existing steel fence post.

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

New bearing trees established:

A 16" douglas fir bears N82°E-42.4 feet, scribed: 1/4S35 BT

A 14" douglas fir bears S13°W-27.4 feet, scribed: 1/4S2 BT

All new bearing trees have washer stamped 'PLS 1106' nailed to face of blaze. Attached sign 54-3 & 54-9, painted face of blaze & a 6" red band around each bearing tree.

Work Done By: WR Wells Title PLS Date 8/10/95 State Registration No. PLS 1106  
or Agency

Certified Cor. Record Prepared? Yes  No  Filed At: GRANT & UMATILLA COUNTY SURV. Date 1/94

REMARKS

This corner was maintained as part of a USFS contract.

A

Index File No. A19 T. 75 R. 31E M. WILLAMETTE Tract or Surv. No.  Cor.

USDA-FOREST SERVICE

Index

File No. A-19

T 7S R. 31E

Merid. WILLAMETTE

CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)

Tract or  
Survey No. \_\_\_\_\_

Cor.  
No. \_\_\_\_\_

R.D. DALE County GRANT

N.F. UMATILLA State OREGON

CORNER DIAGRAM




PHOTO IDENTIFICATION DATA

Photo No. \_\_\_\_\_

Filed At. \_\_\_\_\_

Object Ident. \_\_\_\_\_

Ident. By \_\_\_\_\_

*Signature*

PLANE COORDINATE POSITION DATA

State \_\_\_\_\_ Zone \_\_\_\_\_

X \_\_\_\_\_

Y \_\_\_\_\_

Estab. By \_\_\_\_\_

*Agency*

DESCRIBE CORNER MONUMENT FOUND

No trace of the orig. corner post remains. Found a 2½" Galvanized Iron Pipe, extending 8" above ground with brass cap attached, marked:

U.S. Dept. of the Interior  
Bureau of Land Management

T6S R31E

¼ S35

¼ S2

T7S 1980

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

From Which: An orig. 6" Pine, now a 7" P. Pine, snag, with scribing "BT" visible on a previously opened blaze, bears N66° W 33.0 feet. And an orig. 26" Fir, now a 27" D. Fir snag, partially opened, scars visible bears S38½° E 21.1 feet, and BT's apparently established by the BLM: A 14" D. Fir with scribing "¼ S35 BT" visible on an unhealed single blaze bears N5¼° W 11.3 ft. and a 14" D. Fir with scribing "¼ S2 BT" visible

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

Corner located on wooded north slope, 18 feet north of an E-W fence.

*Signature*  
*Ray J. Langley*

Title  
P.L.S.

Division

Headquarters

Date

12-21-82

7100-52 (3/68)

CORNER RECORD (PERPETUATION)

MONUMENT : DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

9

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

10

Work Done By Gary Langlitz Title Land Surveyor Date 7/27/82 State Registration No. LS 1099  
or Agency

Certified Cor. Record Prepared ?  Yes No Filed At: GRANT AND UMATILLA COUNTY Date 12-82

11

REMARKS

Staff Compass and Steel Tape.

Declination: 19° East

July 27, 1982

Witnesses: Gary L. Langlitz  
Greg Orton  
Jeff Anderson

12


Index File No. A-19 T. 7S R. 31E M. WILLAMETTE Tract or Surv. No.

Cor.

13

Index  
File No. A-19CORNER RECORD (SEARCH)  
(Ref. FSM 7151.4)Tract or  
Survey No. \_\_\_\_\_Cor.  
No. \_\_\_\_\_T 7S R. 31E R.D. Dale County Grant  
Merid. Willamette N.F. Umatilla State Oregon

## CORNER DIAGRAM



## DESCRIBE CORNER MONUMENT FOUND

Material: B Stone Size: 10 x 10 x ?  
Post set originally.

## DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

9" p. pine snag - N 64 W - approx. 33' dist. open  
blaze scribed: B.T. 29" fir-S32E-approx. 21' dist. with  
closed blaze. Facing  $\frac{1}{4}$  corner. Tree is in east, west  
fence. Old location poster on 8" fir 10' sw of  $\frac{1}{4}$  corner.

## PHOTO IDENTIFICATION DATA

Photo No. \_\_\_\_\_  
Filed At. \_\_\_\_\_  
Object Ident. \_\_\_\_\_  
Ident. By \_\_\_\_\_  
*Signature*

## PLANE COORDINATE POSITION DATA

State \_\_\_\_\_ Zone \_\_\_\_\_  
X \_\_\_\_\_  
Y \_\_\_\_\_  
Estpb. By \_\_\_\_\_  
*Agency*

Signature

Bill Moore

Title

Eng. Tech.

Division

Headquarters

Date

3/31/78

7100-52 (3/68)

5

**CORNER RECORD (PERPETUATION)**

GPO 902-873

**MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT**

**ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE**

I placed bearing tree and attention posters on the 2 BT's.

Work Done By \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_ State Registration No. or Agency \_\_\_\_\_

Certified Cor. Record Prepared? Yes No Filed At \_\_\_\_\_ Date \_\_\_\_\_

**REMARKS**

Index File No. T. R. M. Tract or Surv. No. Cor.