Subdivisional Lines, T. 1 S., R.36 E.,W.M.

Chains		Feet
	marked T.1 S.,R.36 E.,S.35,B.T.	
	A fir, 9 ins. diam., brs. S.25°W., 57 lks. dist.,	
	marked T.1 S.,R.36 E.,S.34,B:T.	
	A fir, 6 ins. diam., brs.N.30°W., 5 lks. dist.,	
	marked T.1 S.,R.36 E.,S.27,B.T.	
	Land; mountainous.	
	Soil; sandy loam, 2nd rate.	
	Heavily timbered with fir, tamarack and pine.	
	E. on random line bet. Secs. 26 & 35	
	Var. 23½°E.	
	Descend through timber.	
7.00	Dry bed of creek, course S.E.	
40.00	Set temp. ¼ Sec. Cor.	
40.50	Dry bed of creek, course N.E. Ascend about 400 ft. to	
75.00	Top of ridge, course N.	
80.76	Intersect, 25 lks. N. of the Cor. to Secs. 25, 26, 35 & 36.	
	Thence I run	
	N.89°49' W. on a true line bet. Secs. 26 & 35.	
40.38	Set a basalt stone, 12 x 10 x 6 ins., 8 ins. in ground	
	for ¼ Sec. Cor., marked ¼ on N. face, and raised mound	
	of stone alongside.	
80.76	The Cor. to Secs. 26, 27, 34 & 35.	
	Land; mountainous.	
	Soil; 2nd rate.	
	Timber; fir, pine and tamarack.	
	N. bet. Secs. 26 & 27.	
	Var. 23½°E.	
	Descend about 75 ft. to	
3.50	Dry bed of creek, course S.E. Ascend about 250 ft. to	
24.00	Top of ridge, course S.E.	
40.00	Set basalt stone, 12 x 10 x 5 ins., 8 ins. in ground, for	
	¼ Sec. Cor., marked ¼ on W. face, and raised mound of	
	stone alongside.	
60.00	Bottom of gulch about 200 ft. below ridge, course N.E.	