

Chains

2.947 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the

Ground, for cor. No. 3, Cemetery No. 2, with brass cap

marked

CEM 2
COR 3
1917

The cor. of secs. 10, 11, 14 and 15 bears S.48°49' E.,

25.67 chs. dist.

N.82°10' W., on S. bdy. of cemetery.

3.187 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the

Ground, for cor. No. 4, Cemetery No. 2, with brass cap

marked

CEM 2
COR 4
1917

Cor. No. 3, Cemetery No. 1 bears N.82°10' W., 9.311 chs.

dist.

Thence

N.10°49' E., on W. bdy. of cemetery.

To cor. No. 1, the place of beginning.

Area of Cemetery No. 2, 1.13 acres.

4.017

Dec. 6, 1917.

(Signed)

L. E. Wilkes

U. S. Surveyor

For final Certificate of U. S. Surveyor see Book "E"

APPROVAL

Office of U.S. Surveyor General,
Portland, Oregon, August 26, 1918.

The foregoing field notes of the Retracement-Resurvey of Subdivisional Lines, Subdivision of Section 10 and Survey of Cemeteries in said Section, Township No. 2 North, Range No. 33 East of the Willamette Meridian, Oregon, executed by L. E. Wilkes, U. S. Surveyor, under his special instructions, dated August 20, 1917, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

(Signed)

Edward Worth

U. S. Surveyor General