

## Subdivisions, T. 2, N., R. 36 E.

Chains	
38.00	Leave timber and undergrowth, bears N. and S.
40.00	Set ironstone, 15 x 8 x 6 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face, from which A fir, 24 ins. in diam. bears N.66° E., 260 lks. dist., marked $\frac{1}{4}$ S. 9, B.T. No other trees in limits; raise mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Pits impracticable. Thence along steep S. slope of hill, bears N.60° W., S.60° E.
80.00	Set ironstone, 20 x 12 x 6 ins., 15 ins. in the ground for cor. of secs. 8, 9, 16 and 17, marked with 4 notches on the S. and 4 notches on E. edges. Raise mound of stone, 2 ft. base, $\frac{1}{2}$ ft. high, W. of cor. Pits impracticable. This cor. stands about 300 ft. below summit of divide. Land, mountainous. Soil, loam and stony, 2nd and 4th rate. Timber, pine, fir, tamarack, maple, willow and cherry. Undergrowth, chaparral and willow. Mountainous land, 80.00 chains.
	W. on sectional correction line bet. secs. 8 and 17. Descend along steep S. slope of hill into Line Creek.
25.00	Enter undergrowth, bears N. and S.
29.30	Foot of hill, 1000 ft. below summit of divide. Line Creek, 10 lks. wide, course N. 60° W.
29.50	Ascend through heavy timber, bears N.W., S.E.
32.50	Steeper ascent of mountain, bears N.60° W., S.60° E.
35.00	Leave heavy timber and entering scattering, bears N. and S.
40.00	Set ironstone, 15 x 12 x 6 ins., 10 ins. in ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face, from which A fir, 12 ins. in diam. bears N. 35° W., 80 lks. dist., marked $\frac{1}{4}$ S. 8, B.T. A fir, 12 ins. in diam. bears S. 73° W., 55 lks. dist., marked $\frac{1}{4}$ S. 17, B.T.