

Township 3 N., R. 37 E., W.M.

Chains	
37.00	Ascend steep slope S.70°E.
39.75	Scattering timber and undergrowth.
40.00	A point 300 ft. below the closing Sec. Cor. and set temporary $\frac{1}{4}$ Sec. Cor., W. Bdy. of Sec. 30; from which I find the $\frac{1}{4}$ Sec. Cor., E. Bdy. of Sec. 25, as determined by the remaining stump of witness tree, A pine, 36 ins. diam., marked $\frac{1}{4}$ S.,B.T., bears N., 1 ch. 34 lks. dist.; post missing. Therefore, I set a Basalt Stone, 15 x 12 x 4 ins., 10 ins. in ground, for $\frac{1}{4}$ Sec. Cor., W. Bdy. of Sec. 30, marked $\frac{1}{4}$ on E. face, from which A fir, 17 ins. diam., bears S.54°E., 72 lks. dist., marked $\frac{1}{4}$ S.30, B.T.
40.34	The stump of witness tree, above described, dead and broken, 3 lks. E. of line, is in wrong Sec., therefore, I obliterated the marks thereon and at the true Cor. point
41.34	before determined, set a Basalt Stone, 15 x 12 x 6 ins., 10 ins. in ground, for $\frac{1}{4}$ Sec. Cor., E. Bdy. of Sec. 25, marked $\frac{1}{4}$ on W. face, from which A pine, 15 ins diam., bears N.20°W., 65 lks. dist., marked $\frac{1}{4}$ S.25, B.T.
42.25	Ascend over grassy ridge; bears N.E. & S.W.
52.00	Trail, on summit, bears with ridge; descend thru timber and dense undergrowth.
60.00	Scattering timber on W. slope.
80.00	A point 300 ft. below the $\frac{1}{4}$ Sec. Cor., W. Bdy. of Sec. 30 and set a temporary closing Cor. of Secs. 19 & 30; from which I find the Cor. of Secs. 24 & 25, as determined by the remains of stone mound, decayed post and marked stone, described by the Surveyor-General, bears N., 1 ch. 35 lks. distant; therefore I set a Basalt Stone, 20 x 6 x 5 ins., 15 ins. in ground, for closing Cor. of Secs. 19 & 30, marked CC on E. face, with 4 grooves on N. and 2 grooves on S. faces, from which, A fir, 6 ins. diam., bears S.87 $\frac{1}{4}$ ° E., 95 lks. dist. marked T.3 N., R.37 E., S.30, B.T.