

S. Bdy. T. 3 S., R. 30 E., W. M.

Chains		Feet
	Soil 2nd and 3rd and 1st rate; Good Pine, Tamarack and Fir timber on W $\frac{1}{2}$ mile, Good grass.	
	S. 89° 47' E. on the S. Bdy. of Sec. 35. Var. 19° 45' E.	
	Down open ridge	
40.00	Set stone 17 x 8 x 5 on ridge for $\frac{1}{4}$ Sec. Cor.	150
49.00	Enter timber course. N. E. & S. W.	300
68.00	Creek 12 lks. wide from S. and S. W. to N.	360
80.00	A Pine 4 in. diam. for Cor. to Secs. 35, 36, 1 and 2 A Pine 5 ins. diam. brs N. 30° E 9 lks. dist. " " 15 " " " S. 5° E 28 " " " " 22 " " " S. 70° W 106 " " " " 10 " " " N. 28° W 54 " "	100
	Land; surface irregular and broken, Soil 3rd and 2nd rate. Good Pine, Fir and Tamarack timber on E. 31.00 Chs. Good grass.	
	S. 89° 47' E. on the S. Bdy. of Sec. 36. Var. 20° 30' E	
22.50	Spring branch course N. W.	100
40.00	Set Pine post for $\frac{1}{4}$ Sec. Cor on W. hillside, A Pine 28 ins. diam. brs. N. 3° W. 97 lks dist. " " 16 " " " S. 4° E 58 " "	
48.00	Leave timber S.E. & N. W.	
80.00	The Cor. to Tps 3 and 4 S Rs. 30 and 30 $\frac{1}{2}$ E W. M. Land; surface very irregular and broken, Soil 3rd and 2nd rate, good Pine, Fir and Tamarack timber on W. 48.00 Chs, Good bunch grass. (Note) All stones used for marking corners are basaltic. Nov. 3, 1878.	300