

Exterior Bdy. Lines of T. 3 S., R. 32 E.

Chains		Feet
40.00	Set a basalt stone 16 x 12 x 5 ins. 11 ins. in ground on S. slope for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face. Raised mound of stone along side,	
46.00	Enter timber, course E. & W.	
80.00	Set a basalt stone 14 x 8 x 7 ins. 10 ins. in ground on N. slope for Cor. to Secs., 12, 13, 7 and 18. Marked with 4 notches on S. and 2 notches N. edges.	
	A Fir 10 ins. diam. brs. N. 28° E. 39 lks dist. Marked T. 3 S., R. 33 E., S 7 B.T.	
	A Fir 12 ins. diam. brs. S. 66° E. 52 lks. dist. Marked T. 3 S., R. 33 E. S. 18 B T.	
	A Pine 8 ins. diam. brs. S. 55° W. 129 lks. dist. Marked T. 3 S., R. 32 E. S. 13 B. T.	
	A Fir 6 ins. diam. brs. N. 34 W. 94 lks. dist. Marked T. 3 S. R. 32 E. S. 12 B.T.	
	Land; surface rolling, Soil; 3rd rate, heavily timbered on S. 32 and N. 34 Ghs. Pine, Tamarack and Fir. Also underbrush, Pine, Fir Tamarack, some open glades.	
	N. between Sec. 12 and 7, Var. 20° 30' E	
3.50	A Spring branch, course E.	
26.00	A brook 6 lks. wide, course E. Descent about 150 ft.	
40.00	Set a basalt stone 14 x 8 x 7 ins. 10 ins. in ground for $\frac{1}{4}$ Sec. Cor. on S.E. slope, marked $\frac{1}{4}$ on W. face. A Juniper, 20 ins. diam. brs. N. 76° E. 120 lks. dist. Marked $\frac{1}{4}$ S. B.T. A Pine 14 ins. diam. brs. S. 70° W. 94 lks. dist. Marked $\frac{1}{4}$ S. B.T.	
80.00	Set a basalt stone 20 x 14 x 4 ins. in mound of stone in open glade. N. W. slope on rocky point for Cor. to Secs. 1, 2, 6 and 7, marked with 1 notch on N. and 5 notches on S. edges.	