

Subdivisional Lines of T 4 N., R. 37 E., W.M.

Chains		Feet
	Land; surface rolling Soil; 3rd rate. Heavy timber, except small prairie, tamarack, fir, spruce and hemlock. Alder and yew, underbrush.	
	N. bet. Secs. 25 & 26	
		Var. 19° E.
24.25	Spring branch, course N.W.	
35.50	Same branch, course N.E.	
40.00	Set fir post on steep E. hillside for $\frac{1}{4}$ Sec. Cor. from which A fir, 5 ins. diam. brs. N. 18° E., 90 lks. dist. A fir, 12 ins. diam. brs. N. 58° W. 125 lks. dist.	
70.00	Cross spur to W. side.	
80.00	Set basalt stone, 18 x 12 x 5 on steep N. side of spur, for Cor. to Secs. 23, 24, 25 & 26. A fir, 18 ins. diam. brs. S. 18° E., 335 lks. dist. A fir, 22 ins. diam. brs. S. 86° W., 380 lks. dist.	
	Land; surface very broken and mountainous. Soil; 3rd rate Heavy timber on S. half mile, N. half mile scattering; tamarack, fir, spruce and hemlock. Alder and yew underbrush.	
		August 16th, 1879
	E. on random line bet. Secs. 24 & 25	
		Var. 21° 30' E.
40.00	Set post for temp. $\frac{1}{4}$ Sec. Cor.	
80.26	Intersected E. Bdy., 18 lks. S. of Cor. to Secs. 24 & 25, from which Cor. I run S. 89° 52' W. on a true line bet. Secs. 24 & 25	
		Var. 18° 30' E.
32.00	Cross to S. side of spur	
40.13	Set fir post on S. side of spur in mound of stone for $\frac{1}{4}$ Sec. Cor.	