

Subdivisional Lines of T 4 N., R 37 E., W.M.

Chains		Feet
79.86	Intersected N. and S. line, 38 lks. N. of Cor. to Secs. 23, 24, 25 & 26, from which Cor. I run N. 89° 44' W. on a true line, bet. secs. 23 & 26 Var. 21° 30' E.	
4.50	In gulch, course N	
26.00	On spur, extending N.	
34.00	In gulch, course N.	
39.93	Set basalt stone, 16 x 10 x 5 on N.E. face of spur for $\frac{1}{4}$ Sec. Cor. A fir, 18 ins. diam. brs. N. 35° W., 55 lks. dist. A fir, 13 ins. diam. brs. S. 6° W., 27 lks. dist.	
64.50	On bluff, course N.W. and S.E.	
72.00	Road to Walla Walla, course NW. and SE.	
79.86	The cor. to Sec. 22, 23, 26 & 27 Land; surface very broken and mountainous. Soil; 3rd rate and worthless. Some good timber, but mostly scattering fir, pine and tamarack.	
N. bet. Secs. 22 & 23		
Var. 19° 30' E.		
7.50	Road to Walla Walla, course N.W. and S.E.	
40.00	Set tamarack post on N. slope for $\frac{1}{4}$ Sec. Cor. A tamarack, 4 ins. diam. brs. N. 50° E., 28 lks. dist. A Tamarack, 4 ins. diam. brs. N. 3° W., 4 lks. dist.	
62.00	Spring branch and gulch, course N.E.	
80.00	Set basalt stone on E. side of spur for Cor. to Secs. 14, 15, 22 & 23, from which A pine, 20 ins. diam. brs. N. 53° E., 229 lks. dist. A pine, 48 ins. diam. brs. S. 5° E., 145 lks. dist. A pine, 4 ins. diam. brs. S. 56° W., 138 lks. dist. No other tree near. Land; surface on S. $\frac{1}{2}$ mile, rolling; on N. $\frac{1}{2}$ mile, broken, Soil; 3rd and 2nd rate. Heavy timber in places and in places scattering. Some good farming land on S. $\frac{1}{2}$ mile.	