

Subdivisional Lines of T. 4 N., R. 37 E., W.M.

Chains		Feet
	Descend steep N. slope into Tamarack Basin.	
34.25	Enter dense thicket of fir and tamarack, brs. N. 70° W. and S. 70° E.	
38.20	Abrupt descent over bluffs and slides.	
40.00	The point for $\frac{1}{4}$ Sec. Cor. falls on a ledge, 2 x 2 x 1 ft. above ground. I mark a cross at the exact Cor. point, for $\frac{1}{4}$ Sec. Cor. and mark $\frac{1}{4}$ on W. side of cross, from which, A fir, 10 ins. diam. brs. S. 82° 30' E., 42 lks. dist. marked $\frac{1}{4}$ S. 13 B.T. A fir, 8 ins. diam. brs. N. 7° W., 21 lks. dist. marked $\frac{1}{4}$ S. 14 B.T.	
46.75	Foot of abrupt descent, 800 ft. below summit of ridge.	
46.80	Creek, 10 lks. wide, course N. 30° W. Ascend over spur, bet. Tamarack Basin and Walla Walla River.	
47.00	Leave thicket, and enter very scattering timber, brs. E and W.	
59.20	Top of spur, 300 ft. above creek, brs. N.W. and S.E. Descend steep N. slope into Walla Walla Canyon.	
60 60.10	Perpendicular bluff, 150 ft. high, brs. E. and W.	
66.25	Foot of mountain, 1800 ft. below Sec. Cor. Over sandy bottom, subject to inundation.	
66.90	Walla Walla River, 50 lks. wide, pure water, swift current, along bottom, course S. 70° W. Over sandy bottom subject to inundation.	
68.90	Pack trail, brs. E. and W.	
69.23	Leave bottom land, brs. E. and W., and ascend steep S. slope of mountain. Leave timber, brs. E. and W.	
80.00	Set an ironstone, 30 x 15 x 6 ins., 22 $\frac{1}{2}$ ins. in the ground for Cor. of Secs. 11, 12, 13 & 14, marked with 4 notches on the S. and 1 notch on the E. edges; raised mound of stone, 4 ft. base, 3 ft. high, W. of Cor.; pits impracticable. Land; mountainous Soil; sandy loam and stony, 1st and 4th rate. Timber; fir, tamarack, pine, alder and cottonwood.	