

Subdivisional Lines of T. 4 N., R. 37 E., W.M.

Chains		Feet
	Mountainous land, 80.00 Chs.	
	June 13, 1902.	
	<hr/>	
	N. 89° 46' E. on a random line bet. 12 & 13	
40.00	Set temp. $\frac{1}{4}$ Sec. Cor.	
80.48	Intersect E. Bdy. of the Tp., 21 lks. S. of the Cor. of Secs. 7, 12, 13 and 18, which is a stone, 4 x 12 x 5 ins. above ground, marked and witnessed as described by the surveyor general. Thence I run	
	S. 89° 37' W. on a true line bet. Secs. 12 & 13	
	Descend N.W. face of mountain through very scattering timber.	
29.00	Ravine, 350 ft. deep, course N. 10° W., thence along steep N. slope, over ridges and ravines into the Walla Walla Canyon.	
40.24	Set an ironstone, 18 x 10 x 5 ins. 5 ins. in ground, struck rock, and raised mound of stone around for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on the N. face; raised mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of Cor. Pits impracticable.	
57.50	Foot of mountain, 1500 ft. below sec. Cor. Thence over sandy bottom of Walla Walla River, subject to inundating	
60.13	Walla Walla River, 50 lks. wide, 3 ft. deep, swift cur- rent, course S. 20° W. Ascend	
60.85	Pack trail, brs. N. 20° E. and S. 20° W.	
60.90	Foot of perpendicular bluffs, 25 ft. high, brs. N. and S. Ascend along steep bluff S. slope of mountain	
77.25	Ridge point, 350 ft. above creek, brs. N. and S. Descend	
79.00	Over bluffs, 15 ft. high, brs. N. and S.	
80.45	The Cor. of Secs. 11, 12, 13 and 14 Land; mountainous Soil; stony, 3rd and 4th rate. Timber; scattering pines, firs, alder and cottonwood. Mountainous lands. 80.24 chs.	