

Resurvey of Exterior Bdy. of T 4 N., R. 38 E., W.M. (N. Bdy.)

Chains		Feet
	<p>raised a mound of stone, 2 ft. base, 112 ft. high, N. of Cor.; pits impracticable.</p> <p>Land; mountainous and rolling</p> <p>Soil; stony and gravelly, 3rd and 4th rate</p> <p>Heavily timbered with fir, tamarack, pine and spruce, 13.50 Chs.</p> <p>Undergrowth, fir, pine, tamarack, spruce, huckleberry, willow and bunchgrass.</p> <p>Mountainous, and heavily timbered land, 80.00 Chs.</p>	
	<hr/>	
	S. 89° 59' E. on S. Bdy. of Sec. 32	
	Descending	
15.40	<p>Dry bed of stream, 10 lks. wide, course S.</p> <p>Ascend steep hill; brs. S. 40° E. and N. 40° W.</p> <p>Difference bet. measurements of 40.00 Chs. by two sets of chainmen is 6 lks., position of middle point:</p> <p>By 1st set: 40.03 Chs.</p> <p>By 2nd set: 39.97 Chs., the mean of which is</p>	
40.00	<p>Find no trace of the old standard $\frac{1}{4}$ Sec. Cor. described by the surveyor general as a basalt stone, 16 x 12 x 5 ins. I set a basalt stone, 18 x 14 x 12 ins., 13$\frac{1}{2}$ ins. in the ground, for standard $\frac{1}{4}$ Sec. Cor., marked S. C. $\frac{1}{4}$ on the N. faces, and raised a mound of stone, 2 ft. base 1$\frac{1}{2}$ ft. high, N. of Cor. Pits impracticable.</p>	
58.00	<p>Top of ridge, brs. S. 10° E. and N. 10° W., descend along barren hillside, slopes S. 70° E.</p>	
69.40	<p>Deep ravine, course S. 20° E., thence down slope S.</p>	
78.50	<p>The old standard Cor. for Cors. 32 & 33, set basalt stone 16 x 12 x 5 ins. in mound of stone, marked and witnessed as described by the surveyor general, brs. N. 4 lks. dist. I destroy all trace of this old cor.</p> <p>A point about level with the last Sec. Cor. and the difference in measurement of 80.00 Chs by two sets of chainmen is 6 lks., point of middle point.</p> <p>By 1st set. 80.00 Chs.</p> <p>By 2nd set, 79.97 Chs., the mean of which</p>	