

Resurvey of the Exterior Bdy. of T 4 N., R. 38 E., W.M. (N. Bdy.)

Chains	Feet
	<p>A fir, 10 ins. diam. brs. N. 10° W., 58 lks. dist. marked <math>\frac{1}{4}</math> S. 33, B.T. No other tree available.</p> <p>I raised a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, N. of Cor. Pits impracticable.</p>
53.65	<p>Bottom of ravine, 500 ft. below spur, course S.10° E. Ascend steep hill, brs. N. 10° E. and S. 10° W.</p>
62.15	<p>Top of spur, brs. N. and S., descend steep slope, S. 70° E.</p>
67.40	<p>Ravine, 100 ft. deep, course S. 10° E., ascend</p>
76.00	<p>Top of rocky spur, brs. S. 10° E. and N. 10° W., descend through scattering timber.</p>
77.90	<p>The old standard Cor. of secs. 33 &amp; 34, set basalt stone 14 x 10 x 5 ins., marked and witnessed as described by the surveyor general, brs. S. 19 lks. dist. I destroy all traces of the old standard Sec. Cor.</p> <p>A point 800 ft. below the last Sec. Cor. and the difference in measurement of 80.00 Chs. by two sets of chainmen is 4 lks., position of middle point:</p> <p>By 1st set, 80.02 Chs.</p> <p>By 2nd set, 79.98 Chs., the mean of which is</p>
80.00	<p>Set a basalt stone, 15 x 12 x 8 ins., 10 ins. in the ground, for standard Cor. for Secs. 33 &amp; 34, marked S.C. on N. face, with 3 grooves on E. and W. faces, from which</p> <p>A fir, 24 ins. diam. brs. N. 80° E., 21 lks. dist. marked T 5 N R 38 E., S. 34 B.T.</p> <p>A fir, 8 ins. diam. brs. N. 60° W., 47 lks. dist. marked T 5 N., R. 38 E., S. 33 B.T.</p> <p>Land; mountainous</p> <p>Soil; stony, 4th rate.</p> <p>Timber, pine, fir, tamarack and spruce.</p> <p>Undergrowth; pine fir, tamarack, spruce, chapperal, willow and bunchgrass.</p> <p>Mountainous land, 80.00 Chs.</p> <hr/> <p>S. 89° 57' E. on S. Bdy. of Sec. 34</p> <p>Descending gradually through scattering timber.</p>