

## Resurvey of Exterior Bdy. of T 4 N., R. 38 E., W.M. (N. Bdy.)

Chains		Feet
	A fir, 12 ins. diam. brs. S. 80° W., 73 lks. dist. marked $\frac{1}{4}$ S. 36, B.T.	
51.00	Top of rise; descend across deep canyon	
56.00	Bottom of canyon; ascend over ridge	
62.00	Top of rise; descend over bluff ground	
66.70	The closing Cor. fo T 4 N., R. 38 & 39 E.	
	A point, 700 ft. below the last Sec. Cor. and the standard Cor. of T. 5 N., Rs. 38 & 39 E.; A pine, 32 ins. diam., marked and witnessed as described by the surveyor general.	
	Difference in measurement of 80.00 Chs. by two sets of chainmen is 18 lks.; position of middle point:	
	By 1st set, 80.09 Chs.	
	By 2nd set, 79.91 Chs., the mean of which	
80.00	The true length of the S. Bdy. as originally established 480.00 Chs.	
	Land; mountainous	
	Soil; stony, 4th rate.	
	Timber; scattering pine and fir.	
	Undergrowth, pine, fir, chapparal and bunchgrass.	
	July 19, 1899	
<hr/>		
	Exterior Bdy. of T. 4 N., R 38 E., W.M. (E. Bdy.) As surveyed by George S. Pershin, U.S. Deputy Surveyor. Under Contract No. 304, Dated Sept. 19, 1878.	
	N. on the E. Bdy. of Sec. 13	
	Var. 20° 45' E.	
40.00	Set fir post on nearly level for $\frac{1}{4}$ Sec. Cor.	
	A fir, 9 ins. diam. brs. N. 80° E., 31 lks. dist.	
	A fir, 10 ins. diam. brs. N. 75° W., 24 lks. dist.	
80.00	A tamarack, 5 ins. diam. on nearly level surface for Cor. to Secs. 12, 13, 7 & 18	
	A spruce, 10 ins. diam. brs. N. 41° E., 29 lks. dist.	
	A spruce, 13 ins. diam. brs. S. 44° E., 51 lks. dist.	
	A spruce, 15 ins. diam. brs. S. 48° W., 34 lks. dist.	
	A spruce, 21 ins. diam. brs. N. 42° W., 50 lks. dist.	
	Land; surface mountain ridge.	