

Subdivisional Lines of T 4 N., R 38 E., W.M.

Chains		Feet
	A fir, 12 ins. diam. brs. S. 13° E., 84 lks. dist. marked $\frac{1}{4}$ S 11 B T	
48.00	Foot of descent	
52.75	A trail brs. S. 50° E., and N. 50° W.	
55.25	The Walla Walla River, 100 lks. wide, course S. 60° W.	
58.00	Leave river bottom	
	Thence ascend along S. slope	
80.00	The Cor. of Secs. 2, 3, 10 & 11	
	Land; mountainous	
	Soil; 1st and 2nd rates.	
	Timber, fir, pine, spruce	
	Undergrowth, willow, maple and wild berry	
	Mountainous or heavily timbered land or land covered with dense undergrowth and exceptionally difficult to survey.	
	80.00 Chs.	
<hr/>		
	N. 0° 1' W. on a true line bet. Secs. 2 & 3	
	Ascend steep precipitous slope through scattering timber and scattering undergrowth.	
24.00	500 ft. above sec. Cor. bearing hill changes to N.E. and S.W.	
40.00	Set a basalt stone, 15 x 8 x 8 ins., 10 ins. in the ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face; from which, A fir, 12 ins. diam. brs. N. 63° E., 76 lks. dist. marked $\frac{1}{4}$ S 2 B T A fir, 12 ins. diam. brs. N. 32° W., 107 lks. dist. marked $\frac{1}{4}$ S 3 B T	
80.75	Intersect the first standard parallel N. 15.50 Chs. N. 89° 57' W. of the standard Cor. to Secs. 34 & 35, which is a basalt stone, 15 x 16 x 10 ins. above ground, marked and witnessed as described by the surveyor general. At the point of intersection I set up a basalt stone, 18 x 6 x 6 ins., 12 ins. in the ground for closing Cor. for Secs. 2 & 3, marked C C on S., with 2 grooves on E and 4 grooves on W. face; from which A fir, 24 ins. in diam. brs. S. 13° 30' E., 68 lks. dist., marked T 4 N R 38 E S 2 B T	