

Subdivisional Lines of T 4 N R 38 E., W.M.

Chains		Feet
80.00	<p>Set a basalt stone, 15 x 12 x 8 ins., 10 ins. in the ground for Cor. of Secs. 9, 10, 15 & 16, marked with 3 notches on the E. and 4 notches on the S. edge; from which</p> <p>A fir, 18 ins. in diam. brs. N. 64° E., 71 lks. dist., marked T 4 N R 38 E S 10 B T</p> <p>A fir, 18 ins. in diam. brs. S. 84° E., 72 lks. dist. marked T 4 N R 38 E S 15 B T</p> <p>and raised a mound of stone, 2 ft. base and a ft. and a half high W. of Cor.</p> <p>No other bearing trees available.</p> <p>Land; mountainous</p> <p>Soil; 1st and 2nd rates</p> <p>Timber; fir, pine, spruce</p> <p>Undergrowth; willow, maple and wild berry</p> <p>Mountainous or heavily timbered land or land covered with dense undergrowth and exceptionally difficult to survey.</p> <p>80.00 Chs.</p>	
17.00	<p>W. on a sectional correction line bet. Secs. 9 & 16</p> <p>Ascend steep, precipitous slope through scattering timber and scattering undergrowth.</p> <p>Summit of divide, 150 ft. high, brs. S. 10° E. and N. 10° W.</p> <p>Begin steep descent of W. slope</p>	
40.00	<p>Set a basalt stone, 15 x 10 x 12 ins. 10 ins. in the ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face; from which</p> <p>A fir, 16 ins. in diam. brs. S. 88° W., 144 lks. dist., marked $\frac{1}{4}$ S 16 B T</p> <p>A fir, 16 ins. in diam. brs. N. 83° W., 140 lks. dist., marked $\frac{1}{4}$ S 9 B T</p>	
45.10	<p>A creek, 10 lks. wide, course N.W.</p> <p>Thence ascend steep E. slope</p>	
71.50	<p>Top of spur, 200 ft. high, brs. N. Begin descent.</p>	
80.00	<p>Set a basalt stone, 15 x 8 x 6 ins., 10 ins. in the ground for Cor. of Secs. 8, 9, 16 & 17, marked with 4 notches on the E. and S. edges; from which</p> <p>A fir, 8 ins. in diam. brs. N. 9° E., 55 lks. dist., marked T 4 N R 38 E S 9 B T.</p>	