

Subdivisional Lines of T 4 N R 38 E., W.M.

Chains		Feet
	<p>Undergrowth; willow, maple and wild berry Mountainous or heavily timbered land or land covered with dense undergrowth and exceptionally difficult to survey. 80.14 Chs.</p>	
	<p>From the Cor. of Secs. 9, 10, 15 & 16 on the Sectional Cor. line, I run, N. 0° 2' W. bet. Secs. 9 & 10 Descend along E. slope through scattering timber and dense undergrowth.</p>	
4.75	A dry run, course N. 10° W. Thence gentle ascent along W. slope.	
24.50	Re-cross dry run, course N. 10° E	
31.50	Re-cross ravine, course N.W.	
33.00	Begin ascent of steep S.W. slope	
36.70	Top of spur, 75 ft. high, course N. 60° W., Descend	
40.00	A fir, 16 ins. diam. For $\frac{1}{4}$ Sec. Cor. I mark $\frac{1}{4}$ S 9 on W. and 10 on E. face; from which, <p style="margin-left: 40px;">A fir, 8 ins. diam. brs. N. 80° E., 25 lks. dist. marked $\frac{1}{4}$ S 10 B T</p> <p style="margin-left: 40px;">A fir, 16 ins. diam. brs. S. 30° W., 33 lks. dist. marked $\frac{1}{4}$ S 9 B T</p>	
42.45	Walla Walla River, 50 lks. wide, course W. Thence over river bottom through heavy timber and dense undergrowth.	
48.50	Leave river bottom, brs. E. and W., and begin ascent.	
49.50	A cabin, brs W. about 4.00 Chs.	
67.65	Top of spur, extending W. 100 ft. high, thence along W slope.	
80.00	Set a basalt stone, 15 x 8 x 6 ins. 10 ins. in the ground for Cor. of Secs. 3, 4, 9 & 10, marked with 3 notches on the E. and 5 notches on S. edge; from which, <p style="margin-left: 40px;">A fir, 16 ins. diam. brs. N. 84° 30' E., 41 lks. dist., marked T 4 N R 38 E S 3 B T</p> <p style="margin-left: 40px;">A pine, 12 ins. in diam. brs. S. 44° E., 40 lks. dist., marked T 4 N R 38 E S 10 B T</p> <p style="margin-left: 40px;">A pine, 30 ins. diam. brs. S. 63° W., 38 lks. dist., marked T 4 N R 38 E S 9 B T</p>	