

Subdivisional Lines of T 4 N R 38 E W.M.

Chains		Feet
	N. of Cor.	
78.00	The Cor. of Secs. 5, 6, 7 & 8 Land; mountainous Soil; 1st and 2nd rates Timber; fir, pine, spruce Undergrowth; willow, maple and wild berry Mountainous or heavily timbered land or land covered with dense undergrowth and exceptionally difficult to survey, 78.00 Chs.	
	N. 0° 4' W. on a true line bet. Secs. 5 & 6. Ascend along E. slope over precipitous ground through scattering undergrowth.	
25.00	Ascend S. slope	
40.00	Set a basalt stone, 15 x 10 x 5 ins., 10 ins. in the ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face; from which, A pine, 18 ins. diam. brs. N. 24° 30' E., 187 lks. dist., marked $\frac{1}{4}$ S 5 B T And raised a mound of stone, 2 ft. base, $1\frac{1}{2}$ st. high W. of Cor.	
42.60	Top of divide, 200 ft. high, brs. S.E. and N.W. Begin descent	
55.00	Enter heavy timber, brs. N.E. and S.W.	
67.00	A dry run, brs. E. Thence ascend, through scattering timber and dense undergrowth.	
81.50	Intersect the first standard parallel N. 16.27 Chs. . N. 89° 57' W. of the standard Cor. of Secs. 31 & 32, which is an iron stone, 6 x 12 x 4 ins. above ground, marked and witnessed as described by the surveyor general. At the point of intersection with the first standard paral- lel N. I set a basalt stone, 15 x 5 x 5 ins., 10 ins. in the ground for Closing Cor. for Secs. 5, & 6, marked C C on S. with 5 grooves on the E. and 1 groove on W. face; from which, A pine, 14 ins. in diam. brs. S. 85° 30' E., 276 lks. dist., marked T 4 N R 38 E S 5 B T	