Supplemental Field Notes, Subdivisionals of T 4 N., R. 38 E., W.M.

Chains		Feet
	A fir, 12 ins. diam., brs. N. 82° W., 22 lks. dist., marked T 4 N R 37 E S 24 B T.	
	Retrace bet. Secs. 19 & 24	
	From the Cor. of Secs. 19, 24, 25 & 30, I retrace N. 46' E. bet. Secs. 19 & 24	
40.20	Intersect the ¼ Sec. Cor.	
	I continue retrace N. 10' E., bet. Secs. 19 & 24.	
78.85	Intersect the Cor. of Secs. 13, 18, 19 & 24.	
	The ¼ Sec. Cor. as re-established by me is out of position, but it was re-established in its original position and the Tp. W. has been subdivided; therefore I had no authority to change the postition of the old ¼ Sec. Cor., but in accordance with the Mannual re-established it at its original location.	
	Retrace on the line bet. Secs. 18 & 19	
	I begin at the C.C. of Secs. 17 & 18	
	Thence I retrace	
	S. 89° 41' W. bet. Secs. 18 & 19	
1.76	Intersect the Cor. of Secs. 19 & 20	
	I find the bearing tree in section 20, marked "S 19". I change this marking to S. 20. I find the bearing tree in Sec. 19, marked "S 20." I change this marking to S 19. I continue the retrace.	
41.76	Set temp. ¼ Sec. Cor.	
41.92	Fall 47 lks. S. of the old ¼ Sec. Cor., I continue the retrace.	
80.05	Intersect Cor. of Secs. 13, 18, 19 & 24. Therefore I return to my temp. ¼ Sec. Cor. and proceed to re-establish the ¼ Sec. Cor. at the point of the temp. ¼ Sec. Cor.	
	I set a basalt stone, 15 x 6 x 6 ins., 10 ins., in the ground, for ¼ Sec. Cor., marked ¼ on N. face, from which	
	A fir, 40 ins. diam., brs. N. 7½° E., 119 lks. dist., marked ¼ S 18 B T; and raised a mound of stone, 2 ft. base, 1½ ft. high N. of Cor.	