

1.
 Exterior Lines, Tp. 4 S., R. 31 E. W.M.
 As surveyed by George S. Pershin, U.S. Deputy Surveyor
 Under contract No. 373,
 Dated Sept. 17, 1880.

Chains		Feet
	I begin at the Cor. to Ts. 4 and 5 S. Rs. 30 and 31 E. and with Burts Improved Solar Compass I run, N. on the W. Bdy. of Sec. 31, Var. 20° 15' E.	
4.00	Leave timber, course E. and W.	
20.00	Enter timber, course E. and W.	
25.00	A ravine, course E.	- 80
39.00	Leave timber, course E. and W.	+ 80
40.00	Set basalt stone 15 x 12 x 8 on S.E. slope in mound of stone for $\frac{1}{4}$ Sec. Cor. A Pine 10 ins. diam. brs. S. 12° E. 108 lks. dist. A Pine 7 Ins. diam. brs. S. 5° W. 91 lks. dist.	
61.00	Enter timber, course E. and W.	
80.00	Set a basalt stone 14 x 12 x 5 on N.W. slope for Cor. to Secs. 30, 31, 25 & 36 from which, A Pine 16 ins. diam. brs. N. 62° E. 26 lks. dist. " " 20 " " " S. 72° W. 32 " " A Fir 8 ins. diam. brs. N. 14° W. 38 lks. dist. No trees on S.E. Land; surface undulating, Soil; 3rd and 2nd rate. Some Pine, Fir, and Tamarack timber. Good grass. Land not adapted to farming.	
	N. on the W. Bdy. of Sec. 30, Var. 19° 30' E.	
32.00	Leave heavy timber, course S.E. and N.W.	
40.00	Set basalt stone 18 x 12 x 10 in mound of stone on S.W. slope for $\frac{1}{4}$ Sec. Cor., no trees.	
54.00	Enter timber, course E. and W.	
80.00	Set basalt stone 20 x 12 x 8 on slight N.E. slope for Cor. to Secs. 19, 30, 24 and 25. A Pine 24 ins. diam. brs. N. 48° E. 182 lks. dist. " " 28 " " " S. 38° E. 196 " " " " 10 " " " N. 90° W. 92 " "	
	No tree S.W.	