

Exterior Lines of T. 4 R. 29 E.

Chains		Feet
	A Pine 10 ins. diam. brs. N. 40° E. 48 lks. dist., marked $\frac{1}{4}$ S.B.T.	
	A Pine 20 ins. diam. brs. S. 58° W. 50 lks. dist., marked $\frac{1}{4}$ S.B.T.	
47.00	Leave heavy timber, course E. and W.	
80.00	Set a basalt stone 15 x 8 x 5 ins. 10 ins. in ground on level for Cor. to Secs. 24, 25, 19 and 30, marked with 2 notches on S. and 4 notches on N. edges, from which, A Pine 10 ins. diam. brs. N. 20° E. 67 lks. dist., marked T. 4 S., R. 30 E., S. 19 B.T. A Pine 26 ins. diam. brs. S. 38° E. 168 lks. dist., marked T. 4 S., R. 30 E., S. 30 B.T. A Pine 20 ins. diam. brs. N. 61° W. 72 lks. dist. marked T. 4 S., R. 29 E., S. 24 B.T. Raised mound of stone alongside. No trees in limits on S.W. Land; Surface rolling, Soil; 3rd and 2nd rate, Pine, Tamarack and Fir timber with some underbrush. Some open glades.	
	N. bet. Secs. 19 and 24, Var. 25° 30' E.	
13.50	Wagon road to timber, course E & W.	
29.50	Begin steep descent	
40.00	Set a basalt stone 12 x 10 x 7 ins. 8 ins. in ground on N. slope for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which, A Tamarack 14 ins. diam. brs. N. 69° E. 102 lks. dist. marked $\frac{1}{4}$ S.B.T. A Tamarack 10 ins. diam. brs. S. 44° W. 45 lks. dist. marked $\frac{1}{4}$ S.B.T.	
80.00	Set basalt stone 14 x 10 x 5 ins. 10 ins. in ground on N. side of slope. Ridge extending N.E. and S.W. for Cor. to Secs. 13, 18, 19 and 24., marked with 3 notches on N. and S. edges from which,	