

1.

Exterior Lines, T.4 S., R.32 E., W. M.  
 As surveyed by George S. Pershin, U.S. Deputy Surveyor  
 Under Contract No. 390,  
 Dated May 12, 1881.

Chains	<p>I begin at the Cor. of Tps. 4 &amp; 5 S., Rs., 32 &amp; 33 E., and with Burt's Improved Solar Compass, (Cor., post in mound of stone on prairie), I run</p> <p>N. on range line along E. Bdy. Sec. 36.</p> <p style="text-align: right;">Var. 20° E.</p>	
20.00	Enter timber, course N.E. & S.W. and begin descent of steep bluff.	
32.00	Camas Creek, 80 lks. wide, course S.W.	-300
40.00	Set basalt stone, 16 x 8 x 5 on W. bank of creek for $\frac{1}{4}$ Sec. Cor.	
	<p>A tamarack, 8 ins. diam., brs. S. 12° E., 17 lks. dist.</p> <p>A fir, 8 ins. diam., brs. N. 22° W., 12 lks. dist.</p>	
60.50	Same creek, course S.E.	
66.00	" " " S.W.	
80.00	Set basalt stone, 14 x 12 x 7 on steep S.E. face of creek bluff for Cor. to Secs. 25, 26, 35 & 36.	
	<p>A pine, 10 ins. diam., brs. N. 88° E., 35 lks. dist.,</p> <p>A " 8 " " " S. 38° E., 14 " "</p> <p>A " 14 " " " S. 87° W., 60 " "</p> <p>A " 15 " " " N. 34° W., 58 " "</p>	
	<p>Land; surface S. 20 chs. nearly level; N. 60 chs. very broken.</p> <p>Soil; 3rd &amp; 2nd rate. On N. 60 chs., heavy pine, tamarack and fir timber; S. 20 chs. prairie.</p> <p>Some thick underbrush on N. 60 chs.</p>	
	<p>N. on E. Bdy. of Sec. 25.</p> <p style="text-align: right;">Var. 21° E.</p>	
19.50	On bluff, course N.E. & S.W.	
40.00	Set basalt stone, 14 x 12 x 5 on S.E. slope for $\frac{1}{4}$ Sec. Cor.	
	<p>A pine, 5 ins. diam., brs. N. 80° E., 17 lks. dist.</p> <p>A tamarack, 18 ins. diam., brs. S. 60° W., 3 lks. dist.</p>	
80.00	Set basalt stone, 18 x 10 x 4 on level for Cor. to Secs. 24, 25, 19 & 30.	
	<p>A pine, 20 ins. diam., brs. N. 24° E., 155 lks. dist.</p> <p>A pine, 8 ins. diam., brs. S. 7° E., 105 lks. dist.</p>	