

Subdivisional Lines, T.4 S., R.33 E., W. M.

Chains	
51.25	A spring branch, course S.E. and descended 60 ft.
80.32	Ascent 70 ft.
	Intersected N. & S. line, 28 lks. S. of Cor. to Secs. 9, 10, 15 & 16.
	Thence I run
	S.89°48'W. on true line bet. Secs. 9 & 16.
	Var.20°00'E.
40.16	Set basalt stone, 20 x 14 x 6 ins., 15 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. side, from which
	A pine, 10 ins. diam., brs. N.68°W., 20 lks. dist., marked $\frac{1}{4}$ S., B.T.
	A pine, 10 ins. diam., brs. S.66°E., 24 lks. dist., marked $\frac{1}{4}$ S., B.T.
80.32	The Cor. to Secs. 8, 9, 16 & 17.
	Land; surface undulating and rolling.
	Soil; 3rd & 2nd rate.
	Heavy pine, tamarack & fir timber, with open glades.
	N. bet. Secs. 8 & 9.
	Var.20°30'E.
3.00	Enter timber, E. & W.
24.00	Enter open glade.
40.00	Set basalt stone, 18 x 10 x 5 ins., 12 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. side,
	A pine, 8 ins. diam., brs. N.18°W., 114 lks. dist., marked $\frac{1}{4}$ S., B.T.
	No tree on E. side.
	Raised mound of stone alongside in lieu of pits.
46.00	Enter timber, course E. & W.
65.25	A spring branch, course S.E.
80.00	Set basalt stone, 18 x 12 x 6 ins., 12 ins. in ground, for Cor. to Secs. 4, 5, 8 & 9, marked with 5 notches on S. and 4 notches on E. edges, from which
	A pine, 24 ins. diam., brs. N.56°E., 30 lks. dist., marked T.4 S., R.33 E., S.4, B.T.