

Exterior Lines, T. 5 S., R. 33 $\frac{1}{2}$  E., W. M.  
 As surveyed by Rufus S. Moore, U.S. Deputy Surveyor,  
 Under Contract No. 451,  
 Dated June 12, 1882.

Chains

From the Cor. to Tps. 4 & 5 S., Rs. 33 $\frac{1}{2}$  & 34 E.,

I run

W. on random line on N. Bdy. of Secs. 1, 2, & 3.

Var. 18°15'E.

I set temp.  $\frac{1}{2}$  mile & mile Cors. at each 40 & 80 chs. and  
 at 2 miles, 23 chs. and 38 lks., I

Intersect W. Bdy. of R. 33 $\frac{1}{2}$  E., 5 lks. S. of established  
 Cor. to Tps. 4 & 5, R. 33 $\frac{1}{2}$  E.

The correction will, therefore, be 2 lks. N. to the mile  
 and its course will be S. 89°59'E.

From the Cor. to Tps. 4 & 5 S., R. 33 $\frac{1}{2}$  E.

I run

S. 89°59'E. on true line bet. Secs. 3 & 34.

Var. 18°15'E.

23.38 Set basalt stone, 14 x 13 x 5 ins., 9 ins. in ground, for  
 Cor. to Secs. 2, 3, 34 & 35, marked with 2 notches on  
 E. and 1 notch on W. edges; raised mound of stone, 2 ft.  
 high and 4 $\frac{1}{2}$  ft. base alongside.

Land; rolling.

Soil; 2nd rate.

Timber; scattering pine.

S. 89°59'E. on true line bet. Secs. 2 & 35.

Var. 19°40'E.

7.00 Enter heavy timber.

40.00 Set basalt stone, 16 x 13 x 9 ins., 11 ins. in ground, for

$\frac{1}{4}$  Sec. Cor., marked  $\frac{1}{4}$  on N. face, from which

A pine, 24 ins. diam., brs. S. 7°E., 27 lks. dist.,  
 marked  $\frac{1}{4}$  S., B.T.

A pine, 30 ins. diam., brs. N. 44°W., 94 lks. dist.,  
 marked  $\frac{1}{4}$  S., B.T.

63.00 Creek, 10 lks. wide, runs S.W.

74.00 Leave heavy timber and enter scattering timber.

80.00 Set basalt stone, 24 x 15 x 15 ins., 18 ins. in ground, for  
 Cor. to Secs. 1, 2, 35 & 36, marked with 1 notch on E.