

Exterior Lines, T 5 N R 38 E W M.
 As surveyed by George Williams, U.S. Deputy Surveyor,
 Under Contract No. 176,
 Dated July 20th, 1872.

Chains

From the Cor. for Tps. 5 & 6 N Rs. 37 & 38 E, which I find standing and to agree with the field notes.

I run

E. on S. Bdy. of Sec. 31.

Var. $21\frac{1}{2}^{\circ}$ E.

8.00 Descend hill.

23.00 Bottom of gulch, falls W.

40.00 Set post for $\frac{1}{4}$ Sec. Cor., from which

A fir, 10 ins. diam., brs. N.15°W., 31 lks. dist.

A pine, 7 ins. diam., brs. S.8°W., 23 lks. dist.

45.00 Summit of hill, descend.

49.40 Spring branch, 1 lk. wide, falls N. Ascend.

58.50 Ridge and descend.

80.00 Set post on side hill, from which

A red fir, 18 ins. diam., brs. N.3°W., 44 lks. dist.

A " " 20 " " " N.36°E., 28 " "

A white " 7 " " " S.38°W., 28 " "

A " " 16 " " " S.44°E., 46 " "

For the Cor. of Secs. 5, 6, 31 & 32.

Land; hilly

Timber; pine, fir & tamarack.

E. on S. Bdy. of Sec. 32.

Var. $21\frac{1}{2}^{\circ}$ E.

17.90 Gulch, 90 ft.

A spring, 1 lk. wide, falls N.W.

25.00 Leave timber.

40.00 Set post and mark stone, in mound of earth, with pits, for $\frac{1}{4}$ Sec. Cor.

46.00 Enter timber.

80.00 Set post for Cor. to Secs. 4, 5, 32 & 33, from which

A willow, 5 ins. diam., brs. S.40°W., 18 lks. dist.

A white fir, 18 ins. diam., brs. N.60°W., 38 lks. dist.

A " " 26 " " " S.65°E., 13 " "

A " spruce, 7 " " " N.22°E., 36 " "