

Exterior Lines, T 5 N R 38 E W M.

Chains

20.80 Gulch, falls N.W. Ascend.

40.00 Set post for $\frac{1}{4}$ Sec. Cor. on steep hillside, face N.W.
From a red fir, 8 ins. diam., brs. S.45°W., 4 lks. dist.,

80.00 Set post on summit of trail ridge, in mound of stone for
Cor. to Secs. 1, 2, 35 & 36, from which
A spruce, 7 ins. diam., brs. N.2°E., 49 lks. dist.
No other trees convenient.
Land; mountainous.
Timber; black pine, spruce, tamarack & fir.

E. on S. Bdy. of Sec. 36.

Var. 21 $\frac{3}{4}$ °E.

40.00 Set basalt stone, 27 x 18 x 10, for $\frac{1}{4}$ Sec. Cor.
A pine, 13 ins. diam., brs. N.27°W., 86 lks. dist.
No other trees convenient.

67.00 Ridge falls N.

80.00 Set post, in mound of earth, with pits and planted marked
basalt stone, 6 x 6 x 4, for Cor. to Tps. 5 & 6 N., Rs.
38 & 39 E.
Land; mountainous.
Timber; spruce, fir & tamarack.

Oct. 1, 1872.

Resurvey of part of N. Bdy., T 5 N R 38 E.
As surveyed by Geo. R. Campbell & Wm. E. Campbell (U.S. Dept.
Under their Joint Contract No. 699 & Special (Surveyors.
Dated March 23, 1899. (Instructions.

From the closing Cor. of Secs. 3 & 4, which is a basalt
stone, 12 x 12 x 7 ins., above ground, marked & wit-
nessed, as described in the field notes of subdivisions
returned to the Surveyor General, I run
W. on blank line, N. Bdy. of Secs. 4; at 40 chs. set temp.
 $\frac{1}{4}$ Sec. Cor. N. Bdy. of Sec. 4; at 39.46 chs. intersect
Cor. of Secs. 4, 5, 32 & 33, before described.
Thence I run