

Dependent Resurvey E. Bdy., T 5 N R 38 E W M.

Chains.

N., on true line on E. Bdy. of Sec. 25.

Asc. 185 ft. over SW. slope, through scattering timber & dense undergrowth.

35.20 Spur, slope SE.; desc. 564 ft. over broken NE. slope.

40.01 Proportionate point.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock and in mound of stone to top, for $\frac{1}{4}$ Sec. Cor. of Sec. 25 only, with brass cap, marked

$\frac{1}{4}$ S25
|
1932

from which

A fir, 24 ins. diam., brs. N.85°W., 65 lks. dist., marked $\frac{1}{4}$ S 25 B T.

A fir, 12 ins. diam., brs. N.29°W., 172 lks. dist., marked $\frac{1}{4}$ S 25 B T.

Continue to desc. 691 ft. over broken NE. slope.

61.00 Spring branch, 2 lks. wide, course NE.

64.00 Reser Creek, 6 lks. wide, course S.70°E.; asc. 478 ft. over broken SW. slope.

77.50 Small ravine, course S.20°W.; asc. 20 ft. over SE. slope.

80.02 The old Cor. established for Secs. 19, 24, 25 & 30, which is a basalt stone, 15 x 8 x 6 ins., firmly set, marked with 4 notches on N. and 2 notches on S. edges, and witnessed by a scattered mound of stone to the W.

I now change this Cor. to refer to Secs. 24 & 25 only.

At point for Cor.

Set an iron post, 3 ft. long, 2 ins. diam., 5 ins. in the ground to solid rock and in mound of stone to top, for Cor. of Secs. 24 & 25 only, with brass cap, marked

T5N | T5N
S24 | R39E
S25 | S30
R38E |
1932

from which

A fir, 16 ins. diam., brs. S.87°W., 165 lks. dist., marked T 5 N R 38 E S 25 B T.

A fir, 12 ins. diam., brs. N.74°W., 187 lks. dist., marked T 5 N R 38 E S 24 B T.

Land; mountainous.

Soil; rocky loam; 3rd rate.

Timber; fir, spruce, tamarack, yew & pine.

Undergrowth; vinemaple, huckleberry, alder, syringa, willow, mountain ash, laurel, Oregon grape and buck brush.