

Subdivisional Lines, T 5 N R 38 E W M.

Chains

Ascending through scrubby, partially deadened timber; hill
brs. N. & S.

7.75 Top of rise on ridge; brs. N. & S.; descend steep hill; brs.
N.60°E. and S.60°W.; trail along ridge.

40.12 A fir, 12 ins. diam., for $\frac{1}{4}$ Sec. Cor., I mark $\frac{1}{4}$ S on N. side;
from which

A fir, 12 ins. diam., brs. N.35°E., 14 lks. dist.,
marked $\frac{1}{4}$ S 12 B T.

A fir, 12 ins. diam., brs. S.40°E., 9 lks. dist.,
marked $\frac{1}{4}$ S 13 B T.

64.69 Foot of hill; stream, 5 lks. wide, runs S.70°W.; ascend
through heavy timber; hill brs. N. & S.

80.24 The Cor. of Secs. 11, 12, 13 & 14.

Land; mountainous.

Soil; gravelly & stony, 3rd & 4th rate.

Timber; fir, tamarack, spruce and pine.

Undergrowth; chaparral, fir, yew, spruce, tamarack, pine,
alder, huckleberry, willow & bunch grass.

Mountainous land; 80.24 chs.

July 26, 1899.

N.0°1'W. bet. Secs. 11 & 12.

Over rolling ground through heavy timber.

2.20 Spruce, 20 ins. diam., on line, I mark with 2 notches on
N. & S. sides.

5.00 Descend from divide bet. head waters of Walla Walla River;
brs. N.50°E. and S.50°W.

27.00 Steep descent.

40.00 A point, 700 ft. below the Sec. Cor. and

Set basalt stone, 18 x 8 x 6 ins., 13 $\frac{1}{2}$ ins. in ground, for
 $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face; from which

A fir, 18 ins. diam., brs. S.42 $\frac{1}{2}$ °E., 40 lks. dist.,
marked $\frac{1}{4}$ S 12, B T.

A tamarack, 30 ins. diam., brs. N.55°W., 22 lks. dist.,
marked $\frac{1}{4}$ S 11 B T.