

Subdivisional Lines, T 5 N R 38 E W M.

Chains	
22.00	Top of rise; thence along N. slope of divide.
32.75	Top of spur; brs. N.30°W. and S.30°E.; descend steep side of mountain through scattering timber.
40.10	A point, 600 ft. below Sec. Cor. and Set basalt stone, 20 x 14 x 8 ins., 15 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face; from which A fir, 38 ins. diam., brs. S.60°E., 8 lks. dist., marked $\frac{1}{4}$ S 12 B T. A fir, 24 ins. diam., brs. N.55°W., 26 lks. dist., marked $\frac{1}{4}$ S 1 B T. Thence through heavy timber and dense undergrowth.
49.35	Branch, 10 lks. wide, runs N.50°W.
70.20	Ravine, course N.W.
80.20	The Cor. of Secs. 1, 2, 11 & 12. Land; mountainous. Soil; gravelly & stony, 3rd & 4th rates. Heavily timbered with fir, tamarack; yew, spruce & pine, 72.95 chs. Undergrowth; yew, chaparral, fir, tamarack, spruce, pine, alder, huckleberry, willow & bunch grass. Mountainous land; 80.20 chs.
	N.0°1' W. bet. Secs. 1 & 2. Descending steep slope, N.W., through heavy timber.
2.10	N. Fork of Walla Walla River, 20 lks. wide, flows S.80°W.; ascend steep hill; brs. E. & W.
22.50	Ravine, course S.E.; steeper ascent; brs. N.70° W. and S. 70°E.
38.00	Hill brs. N.30°E. and S.30°W.
40.00	A point, 900 ft. above Sec. Cor. and Set basalt stone, 48 x 12 x 6 ins., 36 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face; from which A fir, 12 ins. diam., brs. N.77°E., 38 lks. dist., marked $\frac{1}{4}$ S 1 B T. A pine, 15 ins. diam., brs. S.25°W., 48 lks. dist.,