

Subdivisional Lines, T 5 N R 38 E W M.

Chains

Mountainous land; 80.08 chs.

N.0°3' W. bet. Secs. 21 & 22.

Ascending through scattering timber; hill brs. N.70°W. & S.70°E.

10.00 Along W. base of bluff, 50 ft. high.

11.00 Top of rise on spur, brs. E. & W.

Descend steep N.W. slope through heavy timber.

28.25 Stream, 2 lks. wide, runs S.70°W.

Ascend steep hill, brs. N.70°W. & S.70°E.

30.00 Leave timber, brs. E. & W.

39.00 Hill brs. N.10°W. and S.10°E.

40.00 A point, 200 ft. above Sec. Cor. and

A rock, in place, 30 x 30 x 30 ins., above ground, on which

I cut a cross (X), at exact Cor. for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face; from which

A fir, 28 ins. diam., brs. S.65°E., 35 lks. dist., marked $\frac{1}{4}$ S 22 B T.

A pine, 12 ins. diam., brs. S.5°W., 64 lks. dist., marked $\frac{1}{4}$ S 21 B T.

July 31st, 1899.

August 1:

52.50 Top of rise on ridge, brs. N.70°W. & S.70°E.

53.00 Steep descent through heavy timber.

54.90 A tamarack, 24 ins. diam., on line, I mark with 2 notches on N. & S. sides.

73.50 Stream, 3 lks. wide, runs N.70°W.

Thence along hillside bearing N.10°W. & S.10°E., through scattering timber.

80.00 A point, 600 ft. below $\frac{1}{4}$ Sec. Cor., and

Set basalt stone, 20 x 14 x 10 ins., 15 ins. in ground, for Cor. of Secs, 15, 16, 21 & 22, marked with 3 notches on S. & E. edges; from which

A tamarack, 28 ins. diam., brs. N.10°E., 1 ch., 40 lks. dist., marked T 5 N R 38 E S 15 B T.