

Subdivisional Lines, T 5 N R 38 E W M.

Chains

- Thence I run
 N.89°51'E. on random line bet. Secs. 10 & 15.
- 40.00 Set temp. $\frac{1}{4}$ Sec. Cor.
- 79.88 Intersect N. & S. line, 12 lks. N. of Cor. of Secs. 10, 11,
 14 & 15.
- Thence I run
 S.89°56'W. on true line bet. Secs. 10 & 15.
 Ascending through heavy timber and undergrowth.
- 1.50 Top of small point bearing N.E.; descend.
- 2.50 Ravine, course N.E.
- Ascend gradually; land slopes N.30°E.
- 19.50 Top of ridge-point, brs. N.
 Descend steep slope N.30°W.
- 25.25 Enter scattering timber and dense undergrowth.
- 31.00 Enter heavy timber.
- 39.96 Set an ironstone, 15 x 12 x 8 ins., 10 ins. in ground, for
 $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face; from which
 A fir, 14 ins. diam., brs. N.31 $\frac{1}{2}$ °E., 8 lks. dist.,
 marked $\frac{1}{4}$ S 10, B T.
 A fir, 11 ins. diam., brs. S.3°E., 28 lks. dist.,
 marked $\frac{1}{4}$ S 15 B T.
- 49.03 Narrow, sharp ravine, 60 ft. deep, course N.10°E.
 Small spring, 50 lks. S. of line;
 Ascend.
- 53.50 Top of densely overgrown ridge, course N.
 Descend.
- 58.28 Bottom of ravine, 60 ft. deep, course N.
 Ascend.
- 63.25 Top of narrow ridge-point, course N.10°W.
 Thence along Northward slope of Butte, through small sized
 timber.
- 67.00 Descend steep, grassy hill, brs. N.70°W. and S.70°E.
- 75.25 Foot of hill; N. Fork of Walla Walla River, 25 lks. wide,
 flows S.W. over stony bottom.
 Thence over narrow, stony flat, through heavy timber.