

Resurvey of a portion of the exterior of T. 5 S., R. 29 E.W.M.

Chains	Feet
	<p>marked T. 4 S., R. 29 E., S. 36 B.T.</p> <p>Land; rolling,</p> <p>Soil; 2nd rate.</p> <p>Heavy Pint timber, 80.25 Chs.</p> <p style="text-align: right;">April 29, 1883</p>
<hr/> <p>Subdivisional Lines of T. 5 S., R. 30 E. W.M. As surveyed by F.W. Campbell, U.S. Deputy Surveyor, Under Contract No. 468 Dated April 12, 1883.</p> <hr/>	
	<p>Survey commenced May 18, 1883, with a Burt's improved Solar Compass.</p> <p>I commenced at the Standard Cor. to Secs. 35 and 36 on the S. bdy. of the tp. which is a basalt stone 20 x 8 x 4 ins., set firmly in the ground, marked S. C. with,</p> <p style="padding-left: 40px;">1 notch on E. and</p> <p style="padding-left: 40px;">5 notches on W. edges, from which</p> <p style="padding-left: 40px;">A Fir 16 ins. diam. brs. N. 44° E. 50 lks. dist. marked T. 5 S., R. 30 E., S. 36 B.T.</p> <p>No trees on N.W. and a mound of stone around Cor. Thence I run,</p> <p>N. bet. Secs. 35 and 36.</p> <p style="text-align: right;">Var. 20° 15' E.</p> <p>Descending abruptly to</p>
18.00	Foot of hill and Snake Creek, 40 lks. wide, runs S.E.
20.00	Ascend hill, course E. and W.
40.00	Set basalt stone 12 x 10 x 8 ins., 8 ins. in ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which,
	A Pine 24 ins. diam. brs. S. 24° E. 57 lks. dist. marked $\frac{1}{4}$ S.B.T.
	A Pine 30 ins. diam. brs. N. 37° W. 52 lks. dist. marked $\frac{1}{4}$ S.B.T.
	Top of hill, course E. and W.
80.00	Set basalt stone 15 x 12 x 8 ins., 10 ins. in ground for Cor. to Secs. 25, 26, 35 and 36, marked with, 1 notch on S. and E. edges, from which,
	A Pine 20 ins. diam. brs. S. 18° E. 102 lks. dist.