

Subdivisional Lines of T. 5 S., R. 32 E., W.M.

Chains		Feet
40.00	Set basalt stone, 18 x 14 x 5 at foot of bluff in creek bottom for $\frac{1}{4}$ Sec. Cor. A Pine, 14 ins. diam. brs. N. 75° E., 48 lks. dist. A Pine, 40 ins. diam. brs S. 75° W., 36 lks. dist.	
46.00	Leavetimber, course N.W. and S.E.	
80.00	Set basalt stone, 18 x 8 x 7 and post in mound of stone on level for Cor. to Secs. 10, 11, 14 and 15. Land; surface undulating, except Creek canyon. Soil; 2nd and 3rd rate. Pine and Tamarack timber on S. 46 Chs. Good grass in prairie.	
<hr/> E. on a random line bet. Secs. 11 and 14 Var. 18° 00' E.		
40.00	Set post for temp. $\frac{1}{4}$ Sec. Cor.	
80.37	Intersected N. and S. line, 28 lks. S. of Cor. to Sec. 11, 12, 13 & 14, from which Cor. I run S. 89° 48' W. on a true line bet. Sec. 11 & 14 Var. 19° 30' E.	
40.18	Set basalt stone, 20 x 10 x 8, on level for $\frac{1}{4}$ Sec. Cor.	
80.37	The Cor. to Sec. 10, 11, 14 & 15. Land; surface undulating, Soil; 2nd and 3rd rate, good grass, some good farming land. June 3, 1881	
<hr/> N. bet. Sec. 10 & 11 Var. 18° 00' E.		
32.00	Enter timber, course E. and W.	
40.00	Set pine post in ground on level for $\frac{1}{4}$ Sec. Cor. A Pine, 5 ins. diam. brs. S. 77° E., 150 lks. dist. A Pine, 9 ins. diam. brs. N. 28° W., 58 lks. dist.	
80.00	Set basalt stone, 14 x 10 x 7 on top of rocky creek bluff for Cor. to Sec. 2, 3, 10 & 11 A Fir, 16 ins. diam. brs. N. 50° E., 102 lks. dist. A Pine, 40 ins. diam. brs. S. 23° E., 262 lks. dist.	