

Chains

A tamarack, 16 ins. diam., brs. N.75°E., 211 lks. dist.
Land; surface very broken.
Soil; 2nd & 3rd rate.
Timber; mostly burnt & dead, occasional green groves of
pine & tamarack.

E. on true line along S. Bdy. of Sec. 36.

Var. 19°45'E.

40.00 Set basalt stone, 18 x 12 x 8, on W. face near top of
ridge, for $\frac{1}{4}$ Sec. Cor.

A fir, 10 ins. diam., brs. N.47°W., 54 lks. dist.

A pine, 4 ins. diam., brs. S.5°W., 48 lks. dist.

46.00 On ridge, course N. & S.

69.00 In deep ravine at spring, opens N.

80.00 Set pine post, 6 ins. sq., on two sides, on point of spur
extending N., for Cor. to Tps. 5 S., Rs. 33 & 34 E., from
which

A tamarack, 8 ins. diam., brs. N.64°W., 56 lks. dist.

A fir, 10 ins. diam., brs. N.48°E., 35 lks. dist.

Land; surface mountainous.

Soil; 2nd & 3rd rate.

Heavy timber on E. $\frac{1}{2}$ mile, W. $\frac{1}{2}$ mile mostly open, fir, tam-
arack & pine.

Sept. 10, 1880.

Exterior Lines, T. 5 S., R. 33 E., W. M.
As surveyed by Geo. S. Pershin, U.S. Deputy Surveyor.
Under Contract No. 410,
Dated July 28, 1881.

I begin at the post, the Cor. to Tps. 5 S., Rs. 33 & 34 E.
on 1st Standard Parallel S., the Cor. is just as I put
it one year ago.

Viz: Pine post marked

T.5 S., R.34 E., S.31 on N.E.

T.5 S., R.33 E., S.36 on N.W.

A tamarack, 8 ins. diam., brs. N.64°W., 56 lks. dist.,
marked T.5 S., R.33 E., S.36.

A fir, 10 ins. diam., brs. N.48°E., 35 lks. dist.,