

Subdivisional Lines, T.5 S., R.33 $\frac{1}{2}$ E., W. M.

Chains

9 ins. in the ground, marked with 2 notches on E. and 1 notch on W. edges; and raised mound of stone, 2 ft. high and 4 $\frac{1}{2}$ ft. base alongside.

Thence I run

S.0°26'W. on true line bet. Secs. 2 & 3.

With same Var.

- 40.13 Set basalt stone, 13 x 12 x 12 ins., 10 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which
- A pine, 4 ins. diam., brs. S.41°E., 17 lks. dist., marked $\frac{1}{4}$ S., B.T.
 - A pine, 30 ins. diam., brs. N.47°W., 122 lks. dist., marked $\frac{1}{4}$ S., B.T.

- 80.13 The Cor. to Secs. 2, 3, 10 & 11.

Land; rolling.

Soil; 2nd rate.

Scattering pine timber.

Good grass.

Oct.30th, 1882.

General Description.

The land in this Township is generally high and rolling; heavily timbered with pine, fir & tamarack of good quality, with some dense undergrowth of fir, pine and tamarack.

The soil is of 2nd & 3rd rate quality, except along the creeks, where there is some good bottom land.