

South Bdy., T.5 S.,R.34 E.,W. M.

Chains

For S. Bdy. of Sec. 31, see T.5 S.,R.33 $\frac{1}{2}$ E.,W. M.

Subdivisional Lines, T.5 S.,R.34 E.,W. M.
As surveyed by Rufus S. Moore, ~~US~~ Deputy Surveyor,
Under Contract No. 451,
Dated June 12, 1882.

From the Standard Cor. to Secs. 33 & 34 on the S. Bdy. of

Tp., which is a post, 4 ins. sq., marked

S C T 5 S R 34 E on N.

S 34 on E. and

S 33 on W. faces, with

3 notches on E. & W. faces,

from which

A pine, 8 ins. diam., brs. N.63°E., 18 lks. dist.,

marked T.5 S.,R.34 E.,S.34,B.T.

A fir, 10 ins. diam., brs. N.45°W., 16 lks. dist.,

marked T.5 S.,R.34 E.,S.33,B.T.

I run

N. bet. Secs. 33 & 34.

Var.20°E.

40.00 Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$

Sec. Cor., from which

A fir, 8 ins. diam., brs. S.52°E., 7 lks. dist.,

marked $\frac{1}{4}$ S.,B.T.

A pine, 6 ins. diam., brs. N.46°W., 20 lks. dist.,

marked $\frac{1}{4}$ S.,B.T.

66.20 Spring branch, 3 lks. wide, in ravine, runs E., 600 ft.

below $\frac{1}{4}$ Sec. Cor.

And ascend.

80.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for

Cor. to Secs. 27, 28, 33 & 34, 400 ft. above spring

branch, marked

T 5 S R 34 E S 27 on N.E.

T 5 S R 34 E S 28 on N.W.

S 33 on S.W. and

S 34 on S.E. faces, with
1 notch on S. and
3 notches on E. edges,