

Subdivisional Lines, T 6 S R 32 E W M.

Chains

12, 13 & 14.

Thence I run

N.89°57'W. on true line bet. Secs. 11 & 14.

With same Var.

- 40.20 Set pine post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S on N. face, from which
- A pine, 8 ins. diam., brs. S.57°E., 6 lks. dist., marked $\frac{1}{4}$ S B T.
- A pine, 8 ins. diam., brs. N.35°W., 2 lks. dist., marked $\frac{1}{4}$ S B T.

- 80.40 The Cor. to Secs. 10, 11, 14 & 15.

Land; rolling.

Soil; 2nd rate.

Densely covered with forests of pine, fir & tamarack timber, 80.40 chs.

N. bet. Secs. 10 & 11.

Var.19°10'E.

Over rolling ground.

- 40.00 Set basalt stone, 12 x 12 x 8 ins., 8 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which
- A pine, 18 ins. diam., brs. S.59°W., 8 lks. dist., marked $\frac{1}{4}$ S B T.
- A pine, 10 ins. diam., brs. N.60°E., 15 lks. dist., marked $\frac{1}{4}$ S B T.
- 80.00 Set pine post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for Cor. to Secs. 2, 3, 10 & 11, marked
- T 6 S S 2 on N.E.
- R 32 E S 11 on S.E.
- S 10 on S.W. and
- S 3 on N.W. faces, with
- 5 notches on S. and
- 2 notches on E. edges,
- from which
- A tamarack, 20 ins. diam., brs. S.10°E., 35 lks. dist.,